Motorized projection screen for wall or ceiling installations










Product specifications:

- Electrically operated projection screen 230 volt (50Hz) with a usage of no more than 0.69 Ampere (158.7 Watt).
- The motor is mounted on the left side an can be reached through a service hatch in the steel casing.
- The motor is mounted inside the roller, 65 cm long, 4 wire, 12 rotations per minute, maintenance free, integrated brake and thermal overload cut-out.
- The end positions are pre-set.
- The 4 wire connection is integrated into the end cap and can be connected to the electric installation with the connector and standard cable.
- Suitable for wall and ceiling mounting with the supplied flexible mounting brackets which can be positioned 100cm from either endcap.
- The steel square casing (23,9x27,6cm) is galvanised on the inside and on the outside powder coated with a matte structure coating (RAL 9010).
- The round slat bar closes of the bottom of the casing.
- The screen fabrics are flame retardant and seamless.
- The projection fabrics have a 5 cm. border all around or have no borders.
- The projection fabrics have a black backing. Standard 3 position wall switch is supplied.
- The projection screen is tested and monitored by the TÜV/GS programme (EN 60335-1: 2002+A1+A11+A12+A2+A13, EN6035-2-97:2006, DIN 19045-5/01.84 and ZEK 01.2-08/12.08) and CE marked and satisfies the strictest quality and safety requirements.

Options: Aspect Ratios: Without borders 16:9 16:10 Available dimensions Minimum width: Maximum width:

PROJECTAN A BRAND OF MILESTONE AV TECHNOLOGIES BV | www.projectascreens.com





		Viewing Area	Dimensions			Border	Net weight
		cm	L1 mm	L2 mm	L3 mm	cm	kg
16:10	223 x 350	213 x 340	3675	2556	3567	5	97
	255 x 400	245 x 390	4175	3056	4067	5	106
	285 x 450	275 x 440	4675	3556	4567	5	115
	316 x 500	306 x 490	5175	4056	5067	5	125
16:9	201 x 350	191 x 340	3675	2556	3567	5	98
	229 x 400	219 x 390	4175	3056	4067	5	105
	258 x 450	248 x 440	4675	3556	4567	5	114
	286 x 500	276 x 490	5175	4056	5067	5	124
4:3	265 x 350	255 x 340	3675	2556	3567	5	98
	300 x 400	290 x 390	4175	3056	4067	5	108
	340 x 450	330 x 440	4675	3556	4567	5	117
	378 x 500	368 x 490	5175	4056	5067	5	131
1:1	350 x 350	340 x 340	3675	2556	3567	5 L/R	101
	400 x 400	390 x 390	4175	3056	4067	5 L/R	114
	450 x 450	440 x 440	4675	3556	4567	5 L/R	125
	500 x 500	490 x 490	5175	4056	5067	5 L/R	137

Available standard resolution projection surfaces

All screen surfaces are seamless in the viewing area.

Matte White

Gain: 1.0 120° Viewing Angle: Base material: Fiberglass

Fire retardancy: B2 Black backing: Yes Opacity rating: > 99 % Yes Seamless: GreenGuard certification: No

B1 / M1 Fire retardancy

Projection surface with B1 / M1 fire retardancy is optionally available. Contact Projecta for feasibility.



Certifications

- Products are manufactured in an ISO14001 certified facility
- Projecta is an ISO 9001 certified company
- REACH Registration, Evaluation, Authorisation and Restriction of Chemical substances.
- RoHS Restriction of Hazardous Substances.

Give exact the sizes of the projection screen you need:

WEEE - Waste Electronic and Electrical Equipment Regulations.





\sim				
Cus	ton	าเรล	atio	n

	Heigth (cm.) x						
Surface:		Border top:	(cm.)	Border bottom:	(cm.)		
RAL color case and	plastic parts: RAL						
☐ Motor positioned on right side		☐ Scree	Screen fabric mounted reversely				
Remarks:	Remarks:						
Accessories - c	ontrol options						
For projection scree	ns with a standard motor /	delivered as standard with	n a wall switc	h			
' '	emote control (868,3 Mhz						
□ Easy Inst	all wireless projectorcoup	ling (868,3 Mhz)					
□ Easy Inst	tall wireless RF wall switch	n (868,3 Mhz)					
□ Easy Install RF re	emote control with project	corcoupling (868,3 Mhz)					
□ Easy Install proje	ectorcoupling with cable						
□ Easy Install IR re	emote control						
□ Easy Install plug	& play relaybox with pote	ential free contacts					
□ Easy Inst	tall plug & play RS232/RS	422 control kit					
□ Easv Inst	tall plug & play RS232/RS	422 with IP control kit					

Accessories - installation

□ Ceiling brackets


□ Keyswitch


- □ Set extension brackets
- □ Set wall clamps




Elpro Large - wall mounting bracket included

(Dimensions in mm)









front view side view

Elpro Large - ceiling mounting bracket included

(Dimensions in mm)







Warranty

Projecta provides a limited 5 year warranty on the Elpro Concept range and a limited 2 year warranty on all other products. The warranty on the motor of electrical screens is 5 year. All warranties are in effect beginning the date the product was invoiced by Projecta.