



Smooth retraction with CSR



Easy Install with plastic brackets

Matte White Viewing Angle: 120° Gain: 1.0 High Contrast Viewing Angle: 100° Gain: 1.1

ProScreen CSR

- High quality manual projection screen with the reliable Controlled Screen Return, available with various aspect ratios and screen surfaces.
- The Projecta Controlled Screen Return (CSR) allows for the projection screen surface to retract gently into the case in a smooth and controlled manner.
- The ProScreen CSR is available with the CSR spring mechanism up to a width of 240 cm.
- The screen locks into place at 13 cm intervals for possible height adjustment.
- Easy to mount on a wall or ceiling thanks to the Easy Install system.
- The case and the projection screen surface can be made to exactly the right size and the case and slat bar are available in any colour for optimal integration into any interior.

Available dimensions

Datalux Viewing Angle: 70° Gain: 1.5

Minimum width: 180 cm | Maximum width: | 280 cm

Other options

- Extended black drop
- · Without border
- Standard (non-CSR) spring



Accessories

- Pull Rod
- BrightSight for safely cleaning the projection surface
- More on page 64

Dimensions and product codes on

101





Triangular slat bar



Integrated mounting brackets


Out color bits as a color bits

16:9 4:3

1:1







SlimScreen

- Basic manual projection screen with spring mechanism.
- Supplied in the most compact case.
- Easy to mount to a wall or ceiling using the integrated mounting brackets on each end cap.
- The screen locks into place at 11 cm intervals for possible height adjustment.
- The intervals are at 15 cm for screen widths of 200 cm.

Available dimensions

Minimum width: 160 cm |
Maximum width: | 240 cm

Other options

Without border



Accessories

- Pull Rod
- BrightSight for safely cleaning the projection surface
- More on page 64

Dimensions and product codes on