

## **SDI to HDMI - True1**

**xVision Converter Series** 





## #XVVSDI2HDMIT1

Professional equipment in mission-critical applications is all about reliability and confidence. So we started with a clean sheet, and built what may soon become your most trustworthy piece of equipment. Introducing the world's first video converters truly designed for the road. Video converters nowadays are used everywhere on profesionnal A/V events, presentations, live shows and tours and often have a critical role. Yet, they are often the weakest link in the signal chain. Low quality connectors, weak enclosure, external consumer-grade power supply, and overall barebones design that all contribute to a generally unreliable piece of equipment. We wanted to change that, so we designed the xVision Video Converters.

Connections

Video Input

3G/HD/SD SDI BNC

**Video Ouput** 

HDMI 1.2 type A with lock system 2 x 3G/HD/SD SDI BNC

Supported Signals

**3G Format Support** 

1080p50, 1080p59.94, 1080p60.

Subject to change without notice

22 April 2021



	HD Format Support	720p50, 720p59.94, 720p60, 1080i50, 1080i59.94, 1080i60, 1080p23.98, 1080PsF23.98, 1080p24, 1080PsF24, 1080PsF25, 1080PsF25, 1080PsF29.97, 1080PsF30
	SD Format Support	525/23.98 NTSC, 525/29.97 NTSC.625/25 PAL.
	SDI Video Sampling	4:2:2 and 4:4:4
	SDI Audio Sampling	Sample rate of 48 kHz and 24 bit.
	SDI Color Space	YUV and RGB
	SDI Auto Switching	Automatically detects incoming signal format.
	SMPTE Standards	425 M Level A & B, 424 M Level A, 292 M, 259 M
Physical	Height	50 mm (1.97 in)
	Depth	180 mm (7.08 in)
	Width	



107 mm (4.21 in)

Weight

1 kg (2.2 lbs)

Environmental

**Relative Humidity** 

0 % to 90 % non-condensing

Power Requirements

**Power Supply** 

Built-in power supply PowerCON True1 in/loop thru

**Power Consumption** 

15W

**Operational Voltage** 

Range

100-240V with True1 connectors

50-60 Hz

**Courtesy Outlet** 

Max 10A, same voltage as input

In the box

xVision converter SDI to HDMI (True1) Locking HDMI male to DVI male (1 m) AC Mains PowerCon cable (1.5 m, specify plug type at ordering)

Certifications





DESIGNED & MANUFACTURED IN CANADA 🌞





