

# DATASHEET

## 19" 1U Splice Box with telescopic-pull out and quick-lock, RAL9005



### Description

- sliding unit with telescopic pull-out, depth adjustable up to 60 mm
- unassembled
- steel sheet 1.5 mm
- colour RAL9005, black
- dimensions (W x H x D) 483 x 44.5 x 280 mm
- 6 x adhesive fiber tray
- cable entry back sided, prepared for cable gland PG16/M20

### General data

Mounting method	482.6 mm (19 inch)-installation
With housing	True
With front plate	True
With pigtails	False
Number of height units	1
Type of connector external	ST
Sliding	ausziehbar

### Dimensions

Height	44.5 mm
Width	483.0 mm
Depth	280.0 mm

This datasheet was created automatically on 18-11-2020 . Technical changes reserved.



# DATASHEET

## 19" 1U Splice Box with telescopic-pull out and quick-lock, RAL9005

### Available variants

Article no.	Title	Suitable for number of couplings/adapters	Colour RAL-number	
53640TS.2	Splicebox 12ST RAL9005, 1U with telescop slide unit	12	black	9005
53640TS.3	Splicebox 24SC(D) RAL9005, 1U with telescop slide unit	24	black	9005
53640TS.4	Splicebox 12SC(D) RAL9005, 1U with telescop slide unit	12	black	9005
53640TS.9	Splicebox 12SC(S) RAL9005, 1U with telescop slide unit	12	black	9005
53640TS.10	Splicebox 24SC(S) RAL9005, 1U with telescop slide unit	24	black	9005
53640TS.12	Spliceb. 24 E2000® RAL9005,1U with telescop slide unit	24	black	9005

### accessory

53012.1	Cable Glands, Standard
53100.21	Splice Holder for Crimp Arc Splices
53025.1-100	Dust Covers for Front- and Distribution-plates
53010.5	Cable gland PG-16
53100.201	Cover for Splice cassette 53100.200
53100.200	Splice Cassette for 2 x Splice Holder

This datasheet was created automatically on 18-11-2020 . Technical changes reserved.

