

DATASHEET

Splicebox sliding unit, with shifted LC-Duplex metal adapter and stripped pigtails, OS2



Description

completely assembled splice box with adapters and coloured pigtails
 metal housing depth adjustable
 cable entries at the rear, incl. 1 x PG16
 6 x self adhesive fiber tray

Special assembly possible at short notice!

General data

Mounting method	482.6 mm (19 inch)-installation
With housing	True
With front plate	True
With pigtails	True
Number of height units	1
Type of connector external	LC-Duplex
Type of connector interior	LC-Duplex
Pigtails prepared	stripped
Sliding	sliding version
Fibre type	Singlemode
Fibre class	OS2
Adapter material	Metall adapter

Dimensions

Height	44.5 mm
Width	483.0 mm
Depth	244.0 mm

Available variants

This datasheet was created automatically on 18-11-2020 . Technical changes reserved.



DATASHEET

Splicebox sliding unit, with shifted LC-Duplex metal adapter and stripped pigtails, OS2

Article no.	Title	Pigtail	With number of couplings/adapters	Adapter colour	Suitable for number of couplings/adapters	Colour RAL-number	
BA71922V.48	Splice box LC 9/125µ a.,48Pigt. stripped / 24 Adapter	48 x LC	24	metal	24	grey	7035
BA71924VTS.24	Splice box LC-APC 50/125µ a.,24Pigt. stripped / 12 Adapter	48 x LC/APC	12	metal	12	black	9005

accessory

53012.1	Cable Glands, Standard
80362.2-10	FO Marking Strips "Warnung vor Laserstrahlung"
39926.1	Miller® Fiber Cleaning Tapes
53010.5	Cable gland PG-16

This datasheet was created automatically on 18-11-2020 . Technical changes reserved.

