



2m HDMI to VGA Cable

No.: 41456

Connect an HDMI source to a VGA monitor

Description

- Connects an HDMI equipped device to a VGA display or projector
- Supports resolutions up to 1920x1200@60Hz
- Supports video mirroring and extended desktop modes
- Integrated USB Power Cable
- 2 year warranty

The Lindy HDMI to VGA Cable is ideal for connecting an HDMI equipped source such as a PC or laptop to a legacy VGA display or projector. It converts the digital signal from the HDMI connection into an analogue VGA signal and supports high definition video resolutions up to 1920x1200@60Hz.

This cable can also be used to add another display to extend available desktop workspace and increase productivity.

Please note that HDCP signals are not supported.

Technical details

Connectors

- Connector A: HDMI Type A Male
- Connector B: VGA Male
- Housing Material:
 - HDMI: ABS
 - VGA:PVC
- USB: PVC
 Connector Plating: Nickel plated
- Pin Construction: Copper
- Pin Plating: Nickel plated
- Dimensions (approx.) WxDxH:
 - HDMI: 54.4x25x10.1mm (2.14x0.98x0.4in)
 VGA:46x34x20mm (1.81x1.34x0.79in)

 - USB: 37x16x7mm (1.46x0.63x0.28in)

Cable Construction

- Length: 2m (6.56ft)
- Standard: HDMI 1.3
- Colour: Black, red USB connector
- Type: Round
- Jacket Diameter: 6mm
- Jacket Material: PVC

- Conductor Material: TC
- Conductor Gauge: 28AWG
- Shielding: Aluminum BRAID

Specifications

- Supported Bandwidth: 4.95GbpsMaximum Resolution: 1920x1200@60Hz
- Nominal Attenuation:
 100MHz~450MHz -2.44--5.099dB
 450MHz~8100MHz -5.094~32.906dB
- Minimum Bend Radius: 60mm
- Operating Temperature: 0°C 75°C (32°F 167°F)
 Storage Temperature: -10°C 80°C (14°F 176°F)

Miscellaneous

- Packaging Type: PolybagWarranty (Years): 2
- Certificated: CE, FCC, RoHS, REACH, UL & California Proposition 65

Purchasing Information

- No.: 41456
- EAN: 4002888414562

This product is also available in other lengths

- 41455 1m (3.28ft)
- 41456 2m (6.56ft)
- 41457 3m (9.84ft)
- 41458 5m (16.40ft)

© LINDY 2021