



# 0.3m Cat.6 S/FTP Network Cable, Grey No.: 47340

RJ45, M/M, 250MHz, Copper, 28AWG

## Description

- Twisted Pair Patch Cable with RJ45 connectors
- Cat.6 S/FTP PIMF
- Integrated snagless connector for latch protection
- Gold plated pins for better conductivity and elimination of signal loss
- 10 year warranty

Cat.6 S/FTP network cable with support for bandwidth up to 250MHz and features a snagless design with gold plated contacts for ethernet standards up to 1GBase-T.

Cat.6 cable for operating frequencies up to 250MHz in shielded version with braid as overall shield and foil shield for the individual wire pairs (S/FTP). Cat.6 cables are widespread throughout the professional sector. They are ideal for Gigabit Ethernet or AV extension applications. These cables are manufactured and tested according to the ISO/IEC 11801 specification. The cables are packaged individually in a polybag.

The gold-plated contacts ensure reliable, corrosion-free connections over extensive periods of time. A robust snagless strain relief design prevents damage to the connector latch during installation and removal.

Available lengths: 0.3m, 0.5m, 1m, 2m, 3m, 5m, 7.5m, 10m.

Available colours: Grey, Blue, Red, Black, White.

## **Technical details**

#### Connectors

- Connector A: RJ45 Male
- Connector B: RJ45 Male
- Housing Material: Polycarbonate
- Connector Plating: Nickel
- Pin Construction: Copper
- Pin Plating: Gold plated
   Dimensional (approx) W/vDv/
- Dimensions (approx.) WxDxH: 22.8x11.6x8.3mm (0.90x0.46x0.33in)

#### **Cable Construction**

- Length: 0.3m (0.98ft)
- Colour: Grey

- Type: Cat.6
  Jacket Diameter: 6.2mm (0.24in)
  Jacket Material: PVC
- Conductor Material: Copper
  Conductor Gauge: 28AWG
  Shielding: Aluminium Braid

## Specifications

- Supported Bandwidth: 250MHz
  Nominal Attenuation: 32.8dB/100m @250MHz
- Monimum Band Radius: 74mm (2.91in)
  Operating Temperature: -10°C 60°C (14°F 140°F)
  Storage Temperature: -20°C 75°C (-4°F 167°F)

# **Miscellaneous**

- Packaging Type: PolybagWarranty (Years): 10
- Certificated: RoHS, REACH, UL, California Proposition 65

## **Purchasing Information**

- No.: 47340
  EAN: 4002888473408

This product is also available in other lengths

- 47340 0.3m (0.98ft)
  47341 0.5m (1.64ft)
- 47342 1m (3.28ft)
  47343 1.5m (4.92ft)

- 47343 2m (6.56ft)
  47345 3m (9.84ft)
  47346 5m (16.44ft)
  47347 7.5m (24.61ft)
  47348 10m (32.81ft)

© LINDY 2021