



5m Cat.6 S/FTP Network Cable, Green

No.: 47751

RJ45, M/M, 250MHz, Copper, 27AWG

Description

- Twisted Pair Patch Cable with RJ45 connectors
- Cat.6 S/FTP PIMF
- Integrated snagless connector for latch protection
- Gold plated pins for better conductivity and elimination of signal loss
- 10 year warranty

Cat.6 S/FTP network cable with support for bandwidth up to 250MHz and features a snagless design with gold plated contacts for ethernet standards up to 1GBase-T.

Cat.6 cable for operating frequencies up to 250MHz in shielded version with braid as overall shield and foil shield for the individual wire pairs (S/FTP). Cat.6 cables are widespread throughout the professional sector. They are ideal for Gigabit Ethernet or AV extension applications. These cables are manufactured and tested according to the ISO/IEC 11801 specification. The cables are packaged individually in a polybag.

The gold-plated contacts ensure reliable, corrosion-free connections over extensive periods of time. A robust snagless strain relief design prevents damage to the connector latch during installation and removal.

Available lengths: 0.3m, 0.5m, 1m, 1.5m, 2m, 3m, 5m, 7.5m, 10m, 15m, 20m, 30m.

Available colours: Blue, Red, Green, Yellow, Black, White, Orange, Purple, Grey.

Technical details

Connectors

- Connector A: RJ45 Male
- Connector B: RJ45 Male
- Housing Material: Polycarbonate
- Connector Plating: Nickel
- Pin Construction: Copper Alloy
- Pin Plating: Gold plated
- Dimensions [approx.] WxDxH: 11.6x22.8x8.3mm [0.46x0.90x0.33in]

Cable Construction

- Length: 5m [16.44ft]
- Colour: Green
- Type: Cat.6
- Jacket Diameter: 6.2mm [0.24in]
- Jacket Material: PVC
- Conductor Material: Copper
- Conductor Gauge: 27AWG
- Shielding: Aluminium Braid

Specifications

- Supported Bandwidth: 250MHz
- Nominal Attenuation: 32.8dB/100m @250MHz
- Minimum Bend Radius: 74mm [2.91in]
- Operating Temperature: -10°C - 60°C [14°F - 140°F]
- Storage Temperature: -20°C - 75°C [-4°F - 167°F]

Miscellaneous

- Packaging Type: Polybag
- Warranty [Years]: 10
- Certificated: RoHS, REACH, UL, California Proposition 65

Purchasing Information

- No.: 47751
- EAN: 4002888477512

This product is also available in other lengths:

- 47745 - 0.3m [0.98ft]
- 47746 - 0.5m [1.64ft]
- 47747 - 1m [3.28ft]
- 47748 - 1.5m [4.92ft]
- 47749 - 2m [6.56ft]
- 47750 - 3m [9.84ft]
- 47751 - 5m [16.44ft]
- 47752 - 7.5m [24.61ft]
- 47753 - 10m [32.81ft]
- 47754 - 15m [49.21ft]
- 47755 - 20m [65.62ft]
- 47756 - 30m [98.43ft]