

9.8 ft. (3 m) USB-C to DisplayPort Cable - 4K 60Hz - Black

Product ID: CDP2DPMM3MB



This USB-C to DisplayPort cable lets you connect your Thunderbolt 3 or USB Type-C enabled device to a 4K DisplayPort monitor with just one cable, providing you with a convenient, clutter-free solution.

Astonishing Picture Quality

The USB C to DisplayPort adapter cable lets you harness the video capabilities that are built into your USB-C connection, to deliver the astonishing quality of Ultra HD to your 4K display and supporting resolutions up to 3840 x 2160.

Plus, the adapter is backward compatible with 1080p displays, which makes it a great accessory for home, office or other work environments.

www.startech.com 1 800 265 1844



Clutter-Free Installation

At 9.8 ft. (3 m) in length, this monitor cable eliminates the need for excess adapters and cabling, ensuring a tidy, professional installation. For installations requiring a shorter connection we also offer a 6 ft. (1.8 m) (<u>CDP2DPMM6B, CDP2DPMM6W</u>) and a 3.3 ft. (1 m) (<u>CDP2DPMM1MB</u>, <u>CDP2DPMM1MW</u>) USB-C to DP cable, enabling you to choose the right cable length for your custom installation needs.

Hassle-Free Setup

To ensure easy operation and installation, this USB C to DisplayPort cable works with both Windows and Mac computers and allows for plug-and-play installation, removing the need for any additional software or drivers.

CDP2DPMM3MB is backed by a 3-year StarTech.com warranty and free lifetime technical support.

Note: Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter.



Certifications, Reports and Compatibility









Applications

- Connect USB-C or Thunderbolt 3 devices to DP displays
- Ideal for home office or hot desk environments
- Experience enhanced imaging with support for 4K 60Hz
- Deliver enriched presentations on the go

Features

- Reduce clutter with a USB-C to DisplayPort adapter and display cable, in-one
- Get astonishing picture quality with support for UHD video resolutions up to 4K 60Hz
- Make the perfect connection with a monitor cable that works with any USB-C enabled laptop
- Hassle-free connectivity with the reversible USB-C connector
- Compatible with Thunderbolt 3 and USB 3.1 Type-C ports that support DP Alt Mode

www.startech.com 1 800 265 1844



Hard-to-find made easy*

Data Sheet

| Connector B 1 - DisplayPort (20 pin) Male Output | | | |
|---|-------------------|-----------------------------|---|
| AV InputUSB Type-CAV OutputDisplayPortChipset IDSTMicroelectronics - STM32F072CBU6 PERICOM - PI3DPX1203PerformanceAudio Specifications7.1 surround soundMaximum Digital Resolutions3840x2160 @ 60 HzSupported Resolutions1024x768 1220x1200 (High-definition 720p) 1920x1200 (High-definition 1080p) 1920x1200 (Sigh-definition 1080p) 1920x1200 | | Warranty | 3 Years |
| AV OutputDisplayPortChipset IDSTMicroelectronics - STM32F072CBU6 PERICOM - PI3DPX1203PerformanceAudio Specifications7.1 surround soundMaximum Digital Resolutions3840x2160 @ 60 HzSupported Resolutions1024x768 1280x720 (High-definition 720p) 1920x1200 1920x1200 (High-definition 1080p) 2560x1400 2560x1600 3840x2160 (Ultra HD 4K)Special Notes / RequirementsNoteYesInvironmental HumidityVour USB-C port must support DisplayPort over U Att mode) in order to work with this adapter.Physical CharacteristicsOperating Temperature OPerating Temperature0%C to 40%C (32°F to 104°F) Storage Temperature OPerating Temperature OPerating TemperaturePhysical CharacteristicsProduct Height0.6 in [1.5 cm] InformationProduct Height Product Udth0.8 in [20 mm]Product Height Product7.8 oz [222 g]Package Height Package Width Package Width3.8 in [20 mm]Package Width Package Width7.9 in [200 mm] <t< th=""><th>Hardware</th><th>Adapter Style</th><th>Cable Adapters</th></t<> | Hardware | Adapter Style | Cable Adapters |
| Chipset IDSTM:croelectronics - STM32F072CBU6 PERCOM - PI3DPX1203PerformanceAudio Specifications7.1 surround soundMaximum Digital Resolutions3840x2160 @ 60 HzSupported Resolutions1024x768 1280x720 (High-definition 720p) 1920x1200 2560x1480 2560x1400 3840x2160 (Ultra HD 4K)Wide Screen SupportedYesConnector (s)Connector A1 - USB-C (24 pin) DisplayPort Alt Mode Male Inp Connector BSpecial Notes / RequirementsNoteYour USB-C port must support DisplayPort over U Att mode) in order to work with this adapter.EnvironmentalHumidity20%-70%RHOperating Temperature0°C to 40°C (32°F to 104°F) Storage Temperature0°C to 40°C (32°F to 104°F) Storage TemperaturePhysical CharacteristicsColorBlackProduct Height0.6 in [1.5 cm] Product Length118.1 in [3000 mm] Product WidthWeight of Product7.8 oz [222 g]Packaging InformationPackage Height8.7 in [22 cm] Pin [200 mm]Package Width7.9 in [200 mm]Shipping (Package) Weight8.2 oz [231 g] | | AV Input | USB Type-C |
| PERICOM - PI3DPX1203 Performance Audio Specifications 7.1 surround sound Maximum Digital Resolutions 3840x2160 @ 60 Hz Supported Resolutions 1024x768 1280x720 (High-definition 720p) 1920x1200 1920x1200 2560x1440 260x1400 3840x2160 (Ultra HD 4K) Wide Screen Supported Yes Connector (s) Connector A 1 - USB-C (24 pin) DisplayPort Alt Mode Male Inp Connector B 1 - DisplayPort (20 pin) Male Output Special Notes / Note Your USB-C port must support DisplayPort over U Requirements Humidity 20%-70%RH Environmental Humidity 0%C to 40°C (32°F to 104°F) More Conge Temperature -40°C to 80°C (-40°F to 158°F) Physical Characteristics Product Height 0.6 in [1.5 cm] Product Udth 0.8 in [20 mm] 18.1 in [3000 mm] Product Height 7.8 oz [222 g] Packaging Information Package Height 8.7 in [22 cm] Package Width 8.7 in [20 mm] 19.1 in [200 mm] Information Package Width 7.9 in [200 mm] | | AV Output | DisplayPort |
| Maximum Digital Resolutions 3840x2160 @ 60 Hz Supported Resolutions 1024x768 Supported Resolutions 1280x720 (High-definition 720p) 1920x1080 (High-definition 1080p) 1920x1200 2560x1440 2560x1440 2560x1600 3840x2160 (Ultra HD 4K) Wide Screen Supported Yes Connector(s) Connector A 1 - USB-C (24 pin) DisplayPort Alt Mode Male Inp Connector B 1 - DisplayPort (20 pin) Male Output Special Notes / Note Your USB-C port must support DisplayPort over U Requirements Humidity 20%-70%RH Operating Temperature 0°C to 40°C (32°F to 104°F) Storage Temperature -40°C to 80°C (-40°F to 158°F) Physical Product Height 0.6 in [1.5 cm] Product Length 118.1 in [3000 mm] Product Uright 0.8 in [20 mm] Product Width 0.8 in [20 mm] Weight of Product 8.7 in [22 cm] Package Height 0.8 in [20 mm] Information Package Uright 8.2 oz [231 g] | | Chipset ID | |
| Supported Resolutions D24x768 1280x720 (High-definition 720p) 1920x1200 2560x1400 2560x1400 2560x1400 2560x1400 2560x1400 2560x1400 2560x1400 2560x1400 2560x1400 2560x1400 2560x1400 2560x1600 3840x2160 (Ultra HD 4K) Connector (s) Connector A 1 - USB-C (24 pin) DisplayPort Alt Mode Male Inp Connector B Connector (s) Connector A 1 - DisplayPort (20 pin) Male Output Special Notes / Requirements Note Your USB-C port must support DisplayPort over U Alt mode) in order to work with this adapter. Environmental Humidity 20%-70%RH Operating Temperature 0°C to 40°C (32°F to 104°F) Operating Temperature 0°C to 80°C (-40°F to 158°F) Physical Characteristics Product Height 0.6 in [1.5 cm] Product Length 18.1 in [3000 mm] Product Width 0.8 in [20 mm] Weight of Product 7.8 oz [222 g] Packaging moremation Package Length 8.7 in [22 cm] Package Length 8.7 in [20 mm] Package Width 7.9 in [200 mm] | Performance | Audio Specifications | 7.1 surround sound |
| 1280x720 (High-definition 720p) 1920x1200 1920x1200 1920x1200 Wide Screen Supported Wide Screen Supported Ves Connector(s) Connector B Connector B In USB-C (24 pin) DisplayPort Alt Mode Male Inp. Connector B Special Notes / Requirements Humidity Operating Temperature Operating Temperature Out USB-C (24 pin) DisplayPort DisplayPort over UAt mode) in order to work with this adapter. Physical Characteristics Product Height Product Height Product Width Weight of Product Veight of Product Packageing Information Physical Chief Product Physical Product Meight Product Height Product Height Neight of Product Product Meight Product Width Neight of Product Product Meight Product Meight Product Width Neight of Product Product Meight Product Meight </td <td>Maximum Digital Resolutions</td> <td>3840x2160 @ 60 Hz</td> | | Maximum Digital Resolutions | 3840x2160 @ 60 Hz |
| Connector(s)Connector A1 - USB-C (24 pin) DisplayPort Alt Mode Male Inp Connector BSpecial Notes / RequirementsNoteYour USB-C port must support DisplayPort over U Alt mode) in order to work with this adapter.EnvironmentalHumidity20%-70%RHOperating Temperature0°C to 40°C (32°F to 104°F) Storage TemperaturePhysical CharacteristicsColorBlackProduct Height0.6 in [1.5 cm] Product Length118.1 in [3000 mm]Packaging InformationPackage Height0.8 in [20 mm]Package Length Package Width8.7 in [22 cm] Package WidthPackage WidthPackage Width Shipping (Package) Weight8.2 oz [231 g] | | Supported Resolutions | 1280x720 (High-definition 720p) 1920x1080 (High-definition 1080p) 1920x1200 2560x1440 2560x1600 |
| Connector B1 - DisplayPort (20 pin) Male OutputSpecial Notes / RequirementsNoteYour USB-C port must support DisplayPort over U Alt mode) in order to work with this adapter.EnvironmentalHumidity20%-70%RHOperating Temperature0°C to 40°C (32°F to 104°F)Storage Temperature-40°C to 80°C (-40°F to 158°F)Physical CharacteristicsProduct Height0.6 in [1.5 cm]Product Length118.1 in [3000 mm]Product Width0.8 in [20 mm]Packaging InformationPackage Height8.7 in [22 cm]Package Width8.7 in [20 mm]Package Width9.9 in [200 mm]Storage Width8.2 oz [231 g] | | Wide Screen Supported | Yes |
| Special Notes / Requirements Note Your USB-C port must support DisplayPort over UAL mode) in order to work with this adapter. Environmental Humidity 20%-70%RH Operating Temperature 0°C to 40°C (32°F to 104°F) Storage Temperature -40°C to 80°C (-40°F to 158°F) Physical Characteristics Color Product Height 0.6 in [1.5 cm] Product Length 118.1 in [3000 mm] Product Width 0.8 in [20 mm] Weight of Product 7.8 oz [222 g] Packaging Information Package Height Package Udth 5.7 in [22 cm] Package Width 7.9 in [200 mm] Storage Weight 8.2 oz [231 g] | Connector(s) | Connector A | 1 - USB-C (24 pin) DisplayPort Alt Mode Male Input |
| Requirements Alt mode) in order to work with this adapter. Environmental Humidity 20%-70%RH Operating Temperature 0°C to 40°C (32°F to 104°F) Storage Temperature -40°C to 80°C (-40°F to 158°F) Physical Characteristics Product Height 0.6 in [1.5 cm] Product Length 18.1 in [3000 mm] 18.1 in [3000 mm] Product Width 0.8 in [20 mm] 20% Packaging Information Package Height 0.8 in [20 mm] Package Length 8.7 in [22 cm] Package Width 5.9 in [200 mm] Package Width 5.9 in [200 mm] | | Connector B | 1 - DisplayPort (20 pin) Male Output |
| Physical CharacteristicsOperating Temperature0°C to 40°C (32°F to 104°F) -40°C to 80°C (-40°F to 158°F)Physical CharacteristicsColorBlackProduct Height0.6 in [1.5 cm]Product Length118.1 in [3000 mm]Product Width0.8 in [20 mm]Weight of Product7.8 oz [222 g]Packaging InformationPackage Height0.8 in [20 mm]Package Length8.7 in [22 cm]Package Width7.9 in [200 mm]Shipping (Package) Weight8.2 oz [231 g] | | Note | Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter. |
| Storage Temperature-40°C to 80°C (-40°F to 158°F)Physical CharacteristicsColorBlackProduct Height0.6 in [1.5 cm]Product Length118.1 in [3000 mm]Product Width0.8 in [20 mm]Weight of Product7.8 oz [222 g]Packaging InformationPackage HeightPackage Length8.7 in [22 cm]Package Width7.9 in [200 mm]Shipping (Package) Weight8.2 oz [231 g] | Environmental | Humidity | 20%-70%RH |
| Physical CharacteristicsColorBlackProduct Height0.6 in [1.5 cm]Product Length118.1 in [3000 mm]Product Width0.8 in [20 mm]Veight of Product7.8 oz [222 g]Packaging InformationPackage HeightPackage Length8.7 in [20 mm]Package Width5.9 in [200 mm]Package Width5.9 in [200 mm] | | Operating Temperature | 0°C to 40°C (32°F to 104°F) |
| Characteristics Product Height 0.6 in [1.5 cm] Product Length 118.1 in [3000 mm] Product Width 0.8 in [20 mm] Weight of Product 7.8 oz [222 g] Packaging Information Package Height Package Width 8.7 in [20 mm] Package Width 9.9 in [200 mm] Ping (Package) Weight 8.2 oz [231 g] | | Storage Temperature | -40°C to 80°C (-40°F to 158°F) |
| Product Length118.1 in [3000 mm]Product Width0.8 in [20 mm]Weight of Product7.8 oz [222 g]Packaging InformationPackage Height0.8 in [20 mm]Package Length8.7 in [22 cm]Package Width7.9 in [200 mm]Shipping (Package) Weight8.2 oz [231 g] | = | Color | Black |
| Product Width0.8 in [20 mm]Weight of Product7.8 oz [222 g]Packaging InformationPackage Height0.8 in [20 mm]Package Length8.7 in [22 cm]Package Width7.9 in [200 mm]Shipping (Package) Weight8.2 oz [231 g] | | Product Height | 0.6 in [1.5 cm] |
| Weight of Product7.8 oz [222 g]Packaging InformationPackage Height0.8 in [20 mm]Package Length8.7 in [22 cm]Package Width7.9 in [200 mm]Shipping (Package) Weight8.2 oz [231 g] | | Product Length | 118.1 in [3000 mm] |
| Packaging InformationPackage Height0.8 in [20 mm]Package Length8.7 in [22 cm]Package Width7.9 in [200 mm]Shipping (Package) Weight8.2 oz [231 g] | | Product Width | 0.8 in [20 mm] |
| Information Package Length 8.7 in [22 cm] Package Width 7.9 in [200 mm] Shipping (Package) Weight 8.2 oz [231 g] | | Weight of Product | 7.8 oz [222 g] |
| Package Width7.9 in [200 mm]Shipping (Package) Weight8.2 oz [231 g] | | Package Height | 0.8 in [20 mm] |
| Shipping (Package) Weight 8.2 oz [231 g] | | Package Length | 8.7 in [22 cm] |
| | | Package Width | 7.9 in [200 mm] |
| What's in the Box Included in Package 1 - USB-C to DisplayPort cable | | Shipping (Package) Weight | 8.2 oz [231 g] |
| | What's in the Box | Included in Package | 1 - USB-C to DisplayPort cable |

www.startech.com 1 800 265 1844



Data Sheet

Product appearance and specifications are subject to change without notice.

www.startech.com 1 800 265 1844