

# MX2-24x24-HDMI20-Audio

## Full 4K Matrix Switcher

The MX2-24x24-HDMI20-Audio is a member of the Lightware HDMI 2.0 standalone matrix switcher family that supports uncompromised 4K UHD resolution at 60Hz 4:4:4 and allows de-embedding audio from and embedding audio to the HDMI stream.

It has an outstanding number of input and output ports resulting in a port density that makes it particularly suitable for fix-install applications and for future-proof operation centers. It is a perfect choice for installations where a huge number of HDMI 2.0 compliant input and output ports are required along with audio inputs and outputs.

This standalone product has 24 HDMI 2.0 inputs and 24 HDMI 2.0 outputs, transmitting up to 4K at 60Hz in 4:4:4 format, while supporting 3D, Dolby TrueHD and DTS-HD Master Audio. Eight of its input ports have audio connectors for embedding analog stereo audio into the HDMI stream, while the audio connectors next to eight output ports can provide de-embedded stereo LPCM audio for amplifiers and audio systems.



### Highlight features

- HDMI 2.0, HDMI 1.x and DVI 1.0 compliant
- Supports conversion from 4K UHD at 60Hz 4:4:4 to 4K UHD at 60 Hz YCbCr 4:2:2
- 4k@60Hz with RGB 4:4:4 color space, 18 Gbps bandwidth
- HDCP 2.2 and HDCP 1.4 compliant with cross conversion capabilities
- Fully non-blocking switching architecture with zero frame delay
- Pixel Accurate Reclocking on each input
- Advanced EDID Management
- Built-in website
- RS-232, Ethernet and USB control options
- LCD and rotary switch for front panel control
- Front to back cooling airflow
- HDR10 and Dolby Vision support
- Optional redundant power supply with 1:1 redundancy
- Analog audio embedding and de-embedding and digital-to-analog conversion of stereo LPCM

### Specification\*

Routing	24 input to 24 output, non-blocking architecture
Speed	18 Gbps per port
Resolution	Up to 4096x2160@60Hz at RGB or YCbCr 4:4:4 (up to 600MHz pixel clock)
Height	4RU
Mounting	Rack mountable, removable rack ears

### Connectors

Power	IEC standard, 110/220V (one for normal build, two for optional redundancy)
Video inputs	19-pole HDMI 2.0
Video outputs	19-pole HDMI 2.0
Audio inputs / outputs	Stereo balanced, 5-pole Phoenix
Serial control	3-pole Phoenix
Ethernet	RJ45
USB	Mini USB B

\* Specifications are subject to change without notice

### Port diagram

