



WR SERIES RACK, WR-37-42

WR-37-42 |

FEATURES & BENEFITS

The WR Series was designed to provide rear access for equipment even when the equipment bays are placed up against a wall or back to back. Factory-assembled in its own host enclosure, the rack frame pulls out and rotates for service access. Specify a WR Series enclosure when easy access to rear equipment connections is required for larger audio, video and security equipment installations but an access aisle is not practical.



- Host enclosure can be pre-installed on-site
- Detachable rack frame can be integrated with equipment and tested off-site
- Requires no additional accessories to roll out and rotate
- Engineered ventilation is optimized for passive thermal management
- Rack frame features built-in cable management tie points
- 4" laser knockouts provided for cable pass-through and ganging multiple racks
- Standard front and rear 10-32 threaded rackrail with marked spaces

SPECIFICATIONS

GENERAL INFO

Finish: Textured Black Powder Coat

UL Standards Tested: UL2416

LISTING AGENCIES/THIRD PARTY CERTIFICATIONS

RoHS: Yes

Greenguard: Yes

UL Listing No: E313734

DIMENSIONS

Usable Depth: 36

Usable Height: 64.75
Capacity Weight (US): 750
Depth (US): 42.875
Height (US): 76.61
Width (US): 24
Rack Units: 37

TECHNICAL INFORMATION

Rackrail Type: 10-32
Static Load Capacity: 750
UL Load Capacity: 750
Material: Steel
Mounting: Horizontal