



EIZO[®]

FlexScan[®] EV2457

24.1" (61.1 cm) LCD Monitor




Innovate Your Office with Daisy Chain

Maintain a Neat Multi-Monitor Environment

With a DisplayPort 1.2 daisy chain, the EV2457 allows neat arrangement of signal cables. Because multiple monitors can be connected in a row, cabling becomes simpler and easier to manage. With the optional short DisplayPort cable PP100, the cable length is perfectly suited for arranging monitors side-by-side.



Before Messy cables.



After Neat and tidy cables!



DisplayPort-In DisplayPort-Out

FlexScan® EV2457

Create a Bright, Lively Office


With the monitor's white cabinet option, your office environment becomes brighter and more lively. In addition, the entire office can be stylishly coordinated with matching white cables.



Included cable cover neatly hides cables

Frameless, Fully-Flat Design

The monitor has a frameless and fully-flat design with miniscule bezels. Paired with the white cabinet option, the bezels become almost invisible.




Speakers channel to the front

Say Goodbye to Tired Eyes

The EV2457 is equipped with functions to prevent eye fatigue even over long periods of use. With reduced eye fatigue, concentration increases, leading to improved productivity.

- Auto brightness control
- 80% blue light reduction
- Anti-glare screen
- Flicker-free screen



Rest Assured with Verified Compatibility

We undertake in-house testing to ensure that the monitor is compatible with various PCs available in the market. We even test daisychain compatibility so that you can buy with confidence.

www.eizoglobal.com/products/flexscan/ev2457/index.html#tab03


Specifications

Model Variations		With FlexStand, Without Stand
Cabinet Color		White, Black
Panel	Type / Backlight	IPS / LED
	Size	24.1" / 61.1 cm
	Native Resolution	1920 x 1200 (16:10 aspect ratio)
	Viewable Image Size (H x V)	518.4 x 324 mm
	Pixel Pitch	0.270 x 0.270 mm
	Display Colors	16.77 million
	Viewing Angles (H / V, typical)	178° / 178°
	Brightness (typical)	350 cd/m ²
	Contrast Ratio (typical)	1000:1
Response Time (typical)	5 ms (Gray-to-gray)	
Video Signals	Input Terminals	DisplayPort (HDCP 1.3), HDMI (HDCP 1.4), DVI-D (HDCP 1.4)
	Output Terminals	DisplayPort (daisy chain)
	Digital Scanning Frequency (H / V)	DVI: 31 - 76 kHz / 59 - 61 Hz DisplayPort: 31 - 76 kHz / 59 - 61 Hz HDMI: 15 - 76 kHz / 49 - 51 Hz and 59 - 61 Hz
USB	Upstream	USB 3.1 Gen 1: Type-B
	Downstream	USB 3.1 Gen 1: Type-A x 4
Audio	Speakers	1.0 W +1.0 W
	Input Terminals	Stereo mini jack, DisplayPort, HDMI
	Output Terminals	Headphones (Stereo mini jack)
Power	Power Requirements	AC 100 - 240 V, 50 / 60 Hz
	Typical Power Consumption	11 W
	Maximum Power Consumption	59 W
Features & Functions	Preset Modes	Color mode (User1, User2, sRGB, Paper, Movie, DICOM)
	Auto EcoView	Yes
	OSD Languages	English, French, German, Italian, Japanese, Simplified and Traditional Chinese, Spanish, Swedish
Physical Specifications	Dimensions (Landscape, W x H x D)	531 x 353.3 - 510.1 x 190 mm
	Dimensions (Portrait, W x H x D)	343.8 x 540.5 - 607.4 x 190 mm
	Dimensions (Without Stand, W x H x D)	531 x 343.8 x 45.5 mm
	Net Weight	5.8 kg / 3.8 kg (without stand)
	Height Adjustment Range	156.8 mm
	Tilt / Swivel / Pivot	35° Up, 5° Down / 344° / 90° (both clockwise and counter clockwise)
	Hole Spacing (VESA Standard)	100 x 100 mm
Environmental Requirements	Operating Temperature	5 - 35 °C
	Operating Humidity (R.H., non condensing)	20 - 80 %
Certifications & Standards (Please contact EIZO for the latest information.)		TCO Certified Generation 8, EPEAT Gold 2009 (US), EPEAT 2018 (US), TÜV/Ergonomics, TÜV/Low blue light content, TÜV/Flicker Free, TÜV/GS, RCM, CE, CB, cTUVus, FCC-B, CAN ICES-3 (B), TÜV/S, PSE, VCCI-B, EPA Energy Star, RoHS, WEEE, China RoHS, CCC, EAC
Dedicated Software	Monitor Control Utility	Screen InStyle supported
Supplied Accessories (May vary by country. Please contact EIZO for details.)	Signal Cables	DisplayPort (2 m)
	Others	AC power cord (2 m), USB cable (2 m), cable cover, screw for VESA mount x 4, setup guide
Warranty		Five Years*

*Usage time is limited to 30,000 hours. Free from bright sub-pixels for 6 months from the date of purchase.

With current LCD technology, a panel may contain a limited number of missing or flickering pixels. If the monitor is left on continuously over a long period of time, dark smudges or burn-in may appear. To maximize the life of the monitor, we recommend the monitor be turned off periodically.

Dimensions(Unit : mm)



EIZO Corporation

153 Shimokashiwano, Hakusan, Ishikawa 924-8566 Japan

Phone: +81-76-277-6794 Fax: +81-76-277-6793

www.eizoglobal.com

All product names are trademarks or registered trademarks of their respective companies. EIZO, the EIZO logo, and FlexScan are registered trademarks of EIZO Corporation in Japan and other countries. Screen InStyle is a trademark of EIZO Corporation. The terms HDMI and HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing, LLC in the United States and other countries. DICOM is the registered trademark of the National Electrical Manufacturers Association for its standards publications relating to digital communications of medical information. VESA is a registered trademark of Video Electronics Standards Association. ENERGY STAR is a registered trademark of the United States Environmental Protection Agency in the United States and other countries. Specifications are subject to change without notice.