



## OG-FiDO-R-MM

---

The OG-FiDO-R-MM offers unmatched flexibility and cost efficiency for 3G-SDI Fiber conversion, allowing for cable runs up to 700 m (2296 ft) for OM4 and 300 m (984 ft) for OM3 for Multi-Mode fiber optic cables - useful for eliminating ground loop problems.

Designed for use in high density openGear 2RU frames including AJA's OG-X-FR frame, new DashBoard software support on Windows®, macOS® and Linux® offers remote control and monitoring of the openGear architecture and provides convenient and industry standard configuration, monitoring and control options over a PC or local network.

<https://www.aja.com/products/og-fido-r-mm>

---

### Video Formats

---

- 150 Mbps - 3 Gbps, format agnostic

### Video Input Digital

---

- 1-Channel Multi-Mode LC Fiber Input, SMPTE-297
- Nominal Wavelength: 850 nm
- Optical Sensitivity: -15dBm (min)

### Video Output Digital

---

- 1-Channel Dual matching 3G-SDI BNC Outputs, SMPTE-259/292/424

### Reclocking

---

- 270 Mbps, 1.483 Gbps, 1.485 Gbps, 2.966 Gbps, 2.970 Gbps - Auto Select
- All other rates are passed through and not reclocked

### User Interface

---

- openGear DashBoard network control software via Windows, macOS or Linux

### Size (w x d x h)

---

- openGear standard form factor, front slot and rear card. Two slots required for each card.

### Weight

---

- 0.5 lb (0.3 kg)

### Power

---

- openGear frame compatible, 2.5 watts max per card

### Environment

---

- Safe Operating Temperature: 0 to 40 C (32 to 104 F)
- Safe Storage Temperature (Power OFF): -40 to 60 C (-40 to 140 F)
- Operating Relative Humidity: 10-90% noncondensing
- Operating Altitude: <3,000 meters (<10,000 feet)