

#### 2 Port USB VGA Cable KVM Switch - USB Powered with Remote Switch

Product ID: SV211USB



The SV211USB 2-Port VGA Cable KVM Switch lets you control two VGA, USB-equipped PCs with a single monitor, keyboard and mouse.

To help organize your desk without sacrificing valuable work space, this VGA USB KVM switch features a compact footprint and integrated KVM cables that can be connected directly to your systems. Plus, the KVM is USB-powered, eliminating the need for a bulky external power adapter and wall outlet.

This VGA KVM switch offers support for resolutions up to 2048x1536, for the ability to drive a high-resolution VGA display. For simple switching between connected systems, the KVM features a convenient push-button remote switch on a 1.5 meter (5ft) cable, as well as keyboard hot-key support and PC or Mac compatible switching software.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

# Certifications, Reports and Compatibility

## **Applications**

- Great for PC test/burn-in computer control, saving the desk space required for two monitors, keyboards and mice
- Perfect for sharing computers and attached peripherals in the home or home office
- Dual system control for single user workstations, increasing user productivity in the office

#### **Features**

• Supports resolutions up to 2048x1536



- Switch PCs via push-button, hot-keys or switching software (included)
- Space-saving design, minimal footprint
- Integrated KVM cables and remote switch
- Switching software supports PC and Mac platforms
- USB Powered No external power adapter required
- Supports hot-plugging
- Remote switch on 1.5m (5ft.) cable

Hardware		
	Warranty	2 Years
	Audio	No
	KVM Ports	2
	PC Interface	USB
	PC Video Type	VGA
	Number of Monitors Supported	1
	Rack-Mountable	No
	Cables Included	Yes
	Daisy-Chain	No
Performance		
	On-Screen Display	No
	IP Control	No
	Hot-Key Selection	Yes
	Port Selection Support	Push Button, Hotkeys, and Software
Connector(s)		
	Console Interface(s)	VGA (15 pin, High Density D-Sub)
		USB Type-A (4 pin) USB 2.0
	Host Connectors	VGA (15 pin, High Density D-Sub)



## USB Type-A (4 pin) USB 2.0

**Software** 

OS Compatibility Windows 2000, XP, Vista, 7, 8, 8.1, 10

Windows Server 2003, 2008 R2, 2012, 2016, 2019

Mac OS 10.x (Tested up to 10.9), 9.x

Special Notes / Requirements

Note OS Compatibility refers to KVM software only - the KVM itself can be

used without software on any platform

**Indicators** 

LED Indicators PC Selection indictor

**Power** 

Power Source USB-Powered

**Environmental** 

Operating Temperature 0C to 40C (32F to 104F)

Storage Temperature -20C to 60C (4F to 140F)

Humidity 0~90% RH Non-Condensing

Physical Characteristics

Color Black

Material Plastic

Cable Length 33.5 in [85 cm]

Product Length 3.5 in [88 mm]

Product Width 2.6 in [66 mm]

Product Height 0.9 in [23 mm]

Weight of Product 11.3 oz [321 g]

Packaging Information

Package Length 9.8 in [25 cm]



Package Width 6.5 in [16.4 cm]

Package Height 2.5 in [63 mm]

Shipping (Package) Weight

15.4 oz [435 g]

What's in the Box

> Included in Package **KVM Switch**

> > Software CD

Instruction Manual

<sup>\*</sup>Product appearance and specifications are subject to change without notice.