

USB C Multiport Video Adapter with HDMI, VGA, Mini DisplayPort or DVI - USB Type C Monitor Adapter to HDMI 1.4 or mDP 1.2 (4K) - VGA or DVI (1080p) - Silver Aluminum

Product ID: CDPVGDVHDMDP



This silver USB-C multiport video adapter offers a portable solution for connecting your USB Type-C laptop to a VGA, DVI, HDMI or Mini DisplayPort display. The adapter is also available in Space Gray (CDPVDHDMDPSG) and Rose Gold (CDPVDHDMDPRG).

Avoid the hassle of carrying different adapters for different displays with this 4-in-1 USB-C adapter. With VGA, DVI, HDMI and mDP output, you can connect your laptop to virtually any display, a convenient plug-and-play solution for travel or Bring Your Own Device (BYOD) applications.

The HDMI and mDP outputs on this USB-C video adapter support UHD 4K resolutions, providing four times the picture quality of high-definition 1080p. All of the outputs (HDMI, mDP, VGA, DVI) can support high-definition resolutions of up to 1920 x 1200.

The USB Type-C adapter has an aluminum housing designed to match your silver MacBook and is compatible with any device that supports USB-C DP Alt Mode. Featuring a built-in USB-C cable with magnetic cable manager, the USB-C video adapter conveniently stores away for easy travel.

The CDPVGDVHDMDP is backed by a StarTech.com 3-year warranty and free lifetime technical support.

Certifications, Reports and Compatibility

Applications

- · Connect to virtually any display while traveling
- Connect your BYOD MacBook to a VGA, DVI, HDMI or mDP display at work or school
- Connect a secondary VGA, DVI, HDMI or mDP monitor to your MacBook



Features

- 4-IN-1 MULTIPORT USB-C VIDEO ADAPTER: USB-C DP Alt Mode to any one of HDMI 1.4 (4K 30Hz & 7.1ch audio), mDP 1.2 (4K 60Hz & 2ch audio), VGA or DVI (1080p), HDCP 2.2/1.4, Thunderbolt 3 compatible
- TOUGH & PORTABLE: Durable aluminum Silver enclosure with a magnetically-secured hideaway cable wrap for on-the-go users in the office, at home, boardrooms, and classrooms
- COMPATIBILITY: USB-C display adapter for Dell XPS/Precision/Latitude, Lenovo ThinkPad X1 Carbon/Extreme, Surface Laptop 3/Surface Book 3, TB3 MacBook Pro/Air, HP EliteBook/Spectre/ZBook, Chromebooks
- TESTED & VERIFIED: USB Type-C adapter tested @ 4K mini DisplayPort (60Hz)/HDMI (30Hz) or 1080p VGA/DVI with TV, monitor & projector brands like Dell, Asus, Acer, LG, Samsung, Sharp, Sony, Epson
- EASY TO USE: Supporting a driverless plug-and-play setup, this adapter is fully compatible with multiple OS platforms: Windows / macOS / Linux / Chrome OS

Hardware

Warranty 3 Years

Active or Passive Adapter Active

AV Input USB-C

AV Output DVI-I (Digital Only) - Single-Link

VGA

Mini DisplayPort - 1.2

HDMI - 1.4

Chipset ID Cypress - CYPD1120

Cypress - CY7C65210

Parade - PS8348B

Parade - PS171

Performance

Maximum Cable Distance 49.9 ft [15.2 m]

To Display

Video Revision DisplayPort 1.2

HDMI 1.4

Maximum Analog 1920 x 1200 @ 60Hz



Resolutions

Maximum Digital Resolutions

3840 x 2160 @ 30Hz

Supported Resolutions

Max HDMI output: 3840 x 2160 @ 30Hz

Max mDP output: 3840 x 2160 @ 60Hz

HDMI and mDP output: 3840 x 2160, 2560 x 1600, 1920 x 1200, 1920

x 1080, 1280 x 720

DVI and VGA output: 1920 x 1200, 1920 x 1080, 1280 x 720

Wide Screen Supported

Audio Specifications HDMI - 7.1 Channel Audio

Yes

VGA - No Audio Support

Mini DisplayPort - 5.1 Channel Audio

DVI - No Audio Support

General Specifications

Only one video output is supported on the video adapter at a time. If multiple connections are made, only one of the outputs will function.

MTBF 654,111 hours

Connector(s)

Connector A USB-C (24 pin) DisplayPort Alt Mode

Connector B Mini-DisplayPort (20 pin)

VGA (15 pin, High Density D-Sub)

DVI-D (25 pin)

HDMI (19 pin)

Special Notes / Requirements

System and Cable Requirements

Your USB-C port must support DisplayPort over USB-C (DP Alt mode)

in order to work with this adapter.

Note Maximum Cable Distance to Display refers to digital video. VGA

distance capabilities are dependent upon the quality of your cabling



Environmental

Operating Temperature 0C to 70C (32F to 158F)

Storage Temperature -10C to 80C (14F to 176F)

Humidity 40%-50%RH

Physical Characteristics

Color Silver

Cable Length 4.3 in [11 cm]

Product Length 4.1 in [10.5 cm]

Product Width 2.2 in [55 mm]

Product Height 0.6 in [15 mm]

Weight of Product 3.8 oz [108 g]

Packaging Information

Package Length 6.7 in [17 cm]

Package Width 5.7 in [14.5 cm]

Package Height 1.2 in [30 mm]

Shipping (Package)

Weight

6.5 oz [184 g]

What's in the Box

Included in Package travel A/V adapter

^{*}Product appearance and specifications are subject to change without notice.