

### USB 3.0 to Gigabit Ethernet Adapter NIC w/ USB Port - White

#### Product ID: USB31000SPTW



The USB31000SPTW USB 3.0 to Gigabit Ethernet Adapter lets you add a Gigabit network port to your Macbook or Ultrabook computer through a USB 3.0 port, and features an integrated USB 3.0 pass-through port that keeps your USB port available for use with other peripherals. The RJ45 port supports 10/100/1000 Mbps Ethernet and is fully compatible with IEEE 802.3i/u/ab standards.

An ideal replacement LAN adapter or laptop accessory, this compact USB 3.0 NIC leverages the 5 Gbps speed of USB 3.0 to provide full gigabit bandwidth and also offers backward compatibility with USB 2.0 systems (speed limited by USB bus).

The adapter supports features such as IPv4/IPv6 packet Checksum Offload Engine (COE) and TCP large send offload to reduce the load on your CPU. Jumbo Frames, full-duplex operation with 802.3x flow control and VLAN tagging are also supported, making this an efficient and full-featured USB network adapter.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

## Certifications, Reports and Compatibility

# **Applications**

- Replacement for a failed built-in Gigabit Ethernet port on a laptop
- Add Gigabit Ethernet capabilities to a desktop or laptop

### **Features**

Integrated USB 3.0 pass-through port



- IEEE 802.3, 802.3u and 802.3ab (10BASE-T, 100BASE-TX, and 1000BASE-T) compatible
- Crossover Detection & Auto-Correction (Auto MDIX)
- IEEE 802.1Q VLAN Tagging support
- Up to 4K Jumbo Frame support
- Supports Checksum Offload (IPv4, IPv6, TCP, UDP) and Large Send Offload
- Compact, lightweight design for maximum portability
- Gigabit Ethernet port through a USB 3.0 / 2.0 connection

Hardware

Warranty 2 Years

Ports 1

Interface RJ45 (Gigabit Ethernet)

Bus Type USB 3.0

USB Pass-Through Yes

Industry Standards IEEE802.3i, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3az

Chipset ID ASIX - AX88179

VIA/VLI - VL811

**Performance** 

Maximum Data Transfer 5 Gbps (USB 3.0)

Rate

2 Gbps (Ethernet - Full-Duplex)

Max Distance 100 m / 330 ft

Type and Rate USB 3.0 - 5 Gbit/s

Compatible Networks 10/100/1000 Mbps

Auto MDIX Yes

Full Duplex Support Yes

Jumbo Frame Support 4K max.

Connector(s)

Connector Type(s) RJ-45



USB Type-A (9 pin) USB 3.0 (5 Gbps)

USB Type-A (9 pin) USB 3.0 (5 Gbps)

**Software** 

OS Compatibility Windows XP, Vista, 7, 8, 8.1, 10

Windows Server 2003, 2008 R2, 2012, 2012 R2, 2016, 2019

macOS 10.6 to 10.15 - <i>VLAN tagging is currently not supported in

macOS</i>

Linux Kernel 2.6.25 to 4.11.x <i>LTS Versions only</i>

Special Notes / Requirements

System and Cable Requirements

Available USB Port

**Indicators** 

LED Indicators 10/100 Link/Activity (Green)

Gigabit Link/Activity (Amber)

**Power** 

Power Source USB-Powered

**Environmental** 

Operating Temperature 0C to 50C (32F to 122F)

Storage Temperature -20C to 60C (-4F to 140F)

Humidity 5~85% RH

Physical Characteristics

Color White

Form Factor Attached Cable

Material Plastic

Cable Length 6.1 in [15.5 cm]

Product Length 5.0 in [12.6 cm]

Product Width 1.4 in [35 mm]



	Product Height	0.7 in [17 mm]
	Weight of Product	1.6 oz [44 g]
Packaging Information		
	Package Length	5.6 in [14.3 cm]
	Package Width	6.7 in [17 cm]
	Package Height	1.1 in [29 mm]
	Shipping (Package) Weight	4.7 oz [132 g]
What's in the Box		
	Included in Package	Instruction Manual
		Driver CD
		USB 3.0 Network Adapter

<sup>\*</sup>Product appearance and specifications are subject to change without notice.