

USB-C to HDMI Adapter - White - 4K 60Hz

Product ID: CDP2HD4K60W



This USB- C^{TM} to HDMI® adapter lets you output HDMI video and audio from a USB Type- C^{TM} device, with support for Ultra HD 4K at 60Hz. The adapter works with USB-C devices that pass a DisplayPort video signal, and it's also compatible with ThunderboltTM 3 ports. The USB-C video adapter features a sleek white design that looks great with your USB Type-C enabled MacBook or HP® ENVY 13.

Astonishing Picture Quality

The adapter lets you harness the video capabilities that are built into your USB Type-C connection, to deliver the astonishing quality of UHD to your 4K 60Hz display. This makes it easier for you to multitask, while working on the most resource-demanding applications imaginable. With this adapter, you can achieve an output resolution of up to $3840 \times 2160p$ at 60Hz, which is perfect for performing high-resolution tasks such as viewing and editing 4K video.

The adapter is backward compatible with 1080p displays, which makes it a great accessory for home, office or other workspace applications.





The Perfect Travel Companion

With its all-white design, this USB-C video adapter is the perfect accessory for your MacBook with USB-C. The adapter is compact and lightweight so it fits easily into your MacBook bag or carrying case, which is great for BYOD (Bring Your Own Device) applications at the office. While the adapter looks great next your Mac and HP ENVY, it also works with any USB-C computer that supports DisplayPort ALT mode, such as your Windows® laptop.

Hassle-Free Connection with USB Type-C

This adapter lets you utilize the versatile USB Type-C port on your portable device. USB Type-C is a reversible connector, so it doesn't matter which way you plug it in. The reversible connector means you will always plug it in correctly on your first try. It saves you the hassle and distraction of repeatedly attempting to connect your laptop to a display or projector, while you're delivering a presentation or speaking to a group.

The CDP2HD4K60W is backed by a 3-year StarTech.com warranty and free lifetime technical support.

Note:

- Your USB-C equipped device must support video to work with this adapter.
- This product may experience display detection issues with certain models of Mac. If you're experiencing
 issues please contact our technical support. For hassle-free compatibility with Mac we recommend
 CDP2HD4K60H.





Certifications, Reports and Compatibility











Applications

- Keep the adapter with you while traveling, to connect to any HDMI monitor, television or projector you come across
- Connect your BYOD MacBook or HP ENVY to an HDMI display at work
- Connect an HDMI display to your USB-C laptop to use as a secondary monitor

Features

- Astonishing picture quality for resource-demanding applications that require 4K resolution up to 60 Hz
- Hassle-free connection with the reversible USB-C connector
- Thunderbolt 3 port compatible
- Maximum portability with a small footprint and lightweight design
- 7.1 audio support



Data Sheet

Hardware AV Toput USB Type-C AV Output HDMI Chipset ID Pards - PS176 STMicroelectronics - STM32F072CBU6 Ports 1 Performance Audio Specifications 7.1 surround sound Maximum Digital Resolutions 3840 x 2160 (Ultra HD 4K) @ 60h2 Supported Resolutions 1024x768 1828x720 1920x1200 2560x1400 2560x1400 2560x1400 2560x1400 2560x1400 2560x1400 2560x1400 2560x1400 2560x1400 2560x1400 Connector A 1 - USB-C (24 pin) DisplayPort Alt Mode Male Input Pecial Notes / Requirements Note 1 - HDMI (19 pin) Female Output Pecial Notes / Requirements Note This video adapter is not compatible with cables that use Reddere" technology. Pecial Notes / Redurer "technology. System and Cable Requirements Your USB-C port must support DisplayPort over USB-C (0P Alt mode) in order to work with this adapter. Physical Characteristics Color White Product Height 0.4 in [1.1 cm] Product Length 5.9 in [15 cm] Product Width 1 in [25 mm] Product Width 2 in [25 mm] Product Width 3.7 in [22 cm] Product Width 3.7 in [22 cm] <		Warranty	3 Years
Chipset ID Parade - PS176 STMicroelectronics - STM32F072CBU6 Ports 1 Performance Audio Specifications Maximum Digital Resolutions Supported Resolutions Mode Screen Supported Wide Screen Supported Tonnector A Connector B Special Notes / Requirements Special Notes / Product Height Characteristics Color Physical Characteristics Color Product Length Product Unith Product Width Wielght of Product Packaging Information Package Height Package Width Package Width Package Width Signary Audio Special Only Special Octor Packaging (Package) Weight Pin 10 z [20 cm] Package Width Package Width Package Width Package) Weight I 10 z [30 g] Package Length Package) Weight I 10 z [30 g] Package Length Package) Weight I 10 z [30 g] Package Length Package) Weight I 10 z [30 g]	Hardware	AV Input	USB Type-C
Performance Audio Specifications Audio		AV Output	HDMI
Performance Audio Specifications 7.1 surround sound Maximum Digital Resolutions 3840 x 2160 (Ultra HD 4K) @ 60hz Supported Resolutions 1024x768 1280x720 1920x1200 2560x1440 2560x1440 2560x1400 3840 x 2160 @ 60Hz Wilde Screen Supported Yes Connector(s) Connector A 1 - USB-C (24 pin) DisplayPort Alt Mode Male Input Connector B 1 - HDMI (19 pin) Female Output Special Notes / Requirements Note This video adapter is not compatible with cables that use RedMere™ technology. System and Cable Requirements Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter. Physical Characteristics Cable Length 3.7 in [9.3 cm] Color White Product Height 0.4 in [1.1 cm] Product Length 5.9 in [15 cm] Product Width 1 in [25 mm] Weight of Product 0.7 oz [21 g] Packaging Information Package Height 0.5 in [12 mm] Package Width 7.9 in [20 cm] Shipping (Package) Weight 1.1 oz [30 g]		Chipset ID	
Maximum Digital Resolutions 3840 x 2160 (Ultra HD 4K) @ 60hz Supported Resolutions 1024x768 1280x720 1920x1080 1920x1200 2560x1440 2560x1600 3840 x 2160 @ 60Hz Wide Screen Supported Yes Connector(s) Connector A 1 - USB-C (24 pin) DisplayPort Alt Mode Male Input Connector B 1 - HDMI (19 pin) Female Output Special Notes / Requirements RedMere ¹⁶ technology. System and Cable Requirements Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter. Physical Characteristics Color White Product Height 0.4 in [1.1 cm] Product Length 5.9 in [15 cm] Product Width 1 in [25 mm] Packaging Information Package Length 8.7 in [22 cm] Package Width 7.9 in [20 cm] Package Width 7.9 in [20 cm]		Ports	1
Supported Resolutions 1024x768 1280x720 1920x1200 2560x1400 2560x1400 2560x1600 3840 x 2160 @ 60Hz Wide Screen Supported Yes	Performance	Audio Specifications	7.1 surround sound
Physical Characteristics Color White Product Height Product Length Product Length Product Widh of Product		Maximum Digital Resolutions	3840 x 2160 (Ultra HD 4K) @ 60hz
Connector(s)Connector A Connector B1 - USB-C (24 pin) DisplayPort Alt Mode Male InputSpecial Notes / RequirementsNoteThis video adapter is not compatible with cables that use RedMere™ technology.System and Cable RequirementsYour USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter.Physical CharacteristicsCable Length3.7 in [9.3 cm]ColorWhiteProduct Height0.4 in [1.1 cm]Product Width1 in [25 mm]Weight of Product0.7 oz [21 g]Packaging InformationPackage Height0.5 in [12 mm]Package Length8.7 in [22 cm]Package Width7.9 in [20 cm]Shipping (Package) Weight1.1 oz [30 g]		Supported Resolutions	1280x720 1920x1080 1920x1200 2560x1440 2560x1600
Special Notes / Requirements Note This video adapter is not compatible with cables that use RedMere™ technology. System and Cable Requirements Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter. Physical Characteristics Cable Length 3.7 in [9.3 cm] Color White Product Height 0.4 in [1.1 cm] Product Length 5.9 in [15 cm] Product Width 1 in [25 mm] Product Width 0.7 oz [21 g] Packaging Information Package Height 0.5 in [12 mm] Package Width 7.9 in [20 cm] Shipping (Package) Weight 1.1 oz [30 g]		Wide Screen Supported	Yes
Special Notes / RequirementsNoteThis video adapter is not compatible with cables that use RedMere™ technology.System and Cable RequirementsYour USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter.Physical CharacteristicsCable Length3.7 in [9.3 cm]ColorWhiteProduct Height0.4 in [1.1 cm]Product Length5.9 in [15 cm]Product Width1 in [25 mm]Weight of Product0.7 oz [21 g]Packaging InformationPackage Height0.5 in [12 mm]Package Width7.9 in [20 cm]Shipping (Package) Weight1.1 oz [30 g]	Connector(s)	Connector A	1 - USB-C (24 pin) DisplayPort Alt Mode Male Input
RequirementsRedMere™ technology.System and Cable RequirementsYour USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter.Physical CharacteristicsCable Length3.7 in [9.3 cm]ColorWhiteProduct Height0.4 in [1.1 cm]Product Length5.9 in [15 cm]Product Width1 in [25 mm]Weight of Product0.7 oz [21 g]Packaging InformationPackage Height0.5 in [12 mm]Package Length8.7 in [22 cm]Package Width7.9 in [20 cm]Shipping (Package) Weight1.1 oz [30 g]		Connector B	1 - HDMI (19 pin) Female Output
Physical Cable Length 3.7 in [9.3 cm] Color White Product Height 0.4 in [1.1 cm] Product Length 5.9 in [15 cm] Product Width 1 in [25 mm] Weight of Product 0.7 oz [21 g] Packaging Information Package Height 8.7 in [22 cm] Package Width 7.9 in [20 cm] Shipping (Package) Weight 1.1 oz [30 g]			
Color White Product Height 0.4 in [1.1 cm] Product Length 5.9 in [15 cm] Product Width 1 in [25 mm] Weight of Product 0.7 oz [21 g] Packaging Information Package Length 8.7 in [22 cm] Package Width 7.9 in [20 cm] Shipping (Package) Weight 1.1 oz [30 g]	_	Note	
Product Height 0.4 in [1.1 cm] Product Length 5.9 in [15 cm] Product Width 1 in [25 mm] Weight of Product 0.7 oz [21 g] Packaging Information Package Length 8.7 in [22 cm] Package Width 7.9 in [20 cm] Shipping (Package) Weight 1.1 oz [30 g]	_		RedMere™ technology. Your USB-C port must support DisplayPort over USB-C (DP
Product Length 5.9 in [15 cm] Product Width 1 in [25 mm] Weight of Product 0.7 oz [21 g] Packaging Information Package Length 8.7 in [22 cm] Package Width 7.9 in [20 cm] Shipping (Package) Weight 1.1 oz [30 g]	Requirements Physical	System and Cable Requirements	RedMere™ technology. Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter.
Product Width 1 in [25 mm] Weight of Product 0.7 oz [21 g] Packaging Information Package Height 0.5 in [12 mm] Package Length 8.7 in [22 cm] Package Width 7.9 in [20 cm] Shipping (Package) Weight 1.1 oz [30 g]	Requirements Physical	System and Cable Requirements Cable Length	RedMere [™] technology. Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter. 3.7 in [9.3 cm]
Weight of Product 0.7 oz [21 g] Packaging Information Package Height 0.5 in [12 mm] Package Length 8.7 in [22 cm] Package Width 7.9 in [20 cm] Shipping (Package) Weight 1.1 oz [30 g]	Requirements Physical	System and Cable Requirements Cable Length Color	RedMere™ technology. Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter. 3.7 in [9.3 cm] White
Packaging Information Package Height 0.5 in [12 mm] Package Length 8.7 in [22 cm] Package Width 7.9 in [20 cm] Shipping (Package) Weight 1.1 oz [30 g]	Requirements Physical	System and Cable Requirements Cable Length Color Product Height	RedMere™ technology. Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter. 3.7 in [9.3 cm] White 0.4 in [1.1 cm]
Package Length 8.7 in [22 cm] Package Width 7.9 in [20 cm] Shipping (Package) Weight 1.1 oz [30 g]	Requirements Physical	System and Cable Requirements Cable Length Color Product Height Product Length	RedMere™ technology. Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter. 3.7 in [9.3 cm] White 0.4 in [1.1 cm] 5.9 in [15 cm]
Package Width 7.9 in [20 cm] Shipping (Package) Weight 1.1 oz [30 g]	Requirements Physical	System and Cable Requirements Cable Length Color Product Height Product Length Product Width	RedMere™ technology. Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter. 3.7 in [9.3 cm] White 0.4 in [1.1 cm] 5.9 in [15 cm] 1 in [25 mm]
Shipping (Package) Weight 1.1 oz [30 g]	Physical Characteristics Packaging	System and Cable Requirements Cable Length Color Product Height Product Length Product Width Weight of Product	RedMere™ technology. Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter. 3.7 in [9.3 cm] White 0.4 in [1.1 cm] 5.9 in [15 cm] 1 in [25 mm] 0.7 oz [21 g]
	Physical Characteristics Packaging	System and Cable Requirements Cable Length Color Product Height Product Length Product Width Weight of Product Package Height	RedMere™ technology. Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter. 3.7 in [9.3 cm] White 0.4 in [1.1 cm] 5.9 in [15 cm] 1 in [25 mm] 0.7 oz [21 g] 0.5 in [12 mm]
What's in the Box Included in Package 1 - USB-C to HDMI adapter	Physical Characteristics Packaging	System and Cable Requirements Cable Length Color Product Height Product Length Product Width Weight of Product Package Height Package Length	RedMere™ technology. Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter. 3.7 in [9.3 cm] White 0.4 in [1.1 cm] 5.9 in [15 cm] 1 in [25 mm] 0.7 oz [21 g] 0.5 in [12 mm] 8.7 in [22 cm]
	Physical Characteristics Packaging	System and Cable Requirements Cable Length Color Product Height Product Length Product Width Weight of Product Package Height Package Length Package Width	RedMere™ technology. Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter. 3.7 in [9.3 cm] White 0.4 in [1.1 cm] 5.9 in [15 cm] 1 in [25 mm] 0.7 oz [21 g] 0.5 in [12 mm] 8.7 in [22 cm] 7.9 in [20 cm]

Product appearance and specifications are subject to change without notice.