



2m USB 3.0 Type A Extension Cable, Anthra Line

No.: 36762

USB Type A male to A female

Description

- Professional choice USB 3.0 Type A to A Extension cable for commercial and high performance AV and IT installations
- Supports SuperSpeed data transfer speeds up to 5Gbps, compatibel to USB 3.1 Gen1 / USB 3.2 Gen1
- Robust PVC housing, gold plated connectors and contacts
- Triple shielded cable, corrosion resistant tinned copper conductors
- SuperSpeed, USB 3.0, 5Gbps; 10 year warranty

From the Lines cable connectivity concept developed by Lindy, Anthra Line USB 3.0 Type A to A Extension cables are the professional choice for high performance connections in commercial AV and IT installations.

Anthra Line USB 3.0 cables are premium connections that feature triple shielded construction with copper conductors for performance and corrosion resistance. High quality gold plated contacts and connectors maintain optimal signal integrity and maximum reliability.

 $The \ SuperSpeed\ protocol\ is\ supported\ with\ up\ to\ 5Gbps\ bandwidth\ to\ allow\ the\ rapid\ transfer\ of\ large\ data\ volumes.$

Anthra Line USB 3.0 Type A to A Extension cables are available in lengths from 0.5m, 1m, 2m and 3m

Technical details

Connectors

- Connector A: USB 3.0 Type A Male
- Connector B: USB 3.0 Type A Female
- Housing Material: PVC
- Connector Plating: Gold Plated
- Pin Construction: Copper
- Pin Plating: Gold Plated
- Dimensions, USB A Male (approx.) WxDxH: 15.5x35x7.8mm (0.61x1.38x0.31in)
- Dimensions, USB A Female (approx.) WxDxH: 17x35x9.8mm (0.67x1.38x0.39in)

Cable Construction

- Length: 2m (6.56ft)
- Standard: USB 3.0
- Colour: Black

- Type: Round
- Jacket Diameter: 5.5mm (0.22in)
- Jacket Material: PVC
- Conductor Material: Tinned Copper
- Conductor Gauge: 24/28/30AWG
- Shielding: Aluminium Braid 85%

Specifications

- Supported Bandwidth: 5Gbps
- Maximum Resolution: -
- Nominal Attenuation: 0.5-5m: 0.5MHz-7.5GHz
- Minimum Bend Radius: 48mm (1.89in)
- Operating Temperature: 0°C 60°C (32°F 140°F)
- Storage Temperature: 0°C 60°C (32°F 140°F)

Miscellaneous

- Packaging Type: Polybag
- Warranty (Years): 10
- Certificated: RoHS, REACH, UL

Purchasing Information

- No. 36762
- EAN: 4002888367622

© LINDY 2021