



3m USB 2.0 Type C to A Cable, Anthra Line

No.: 36888

USB Type C Male to A Male

Description

- Professional choice USB 2.0 Type C to A cable for commercial and high performance AV and IT installations
- Supports data transfer speeds up to 480Mbps
- Robust PVC housing, gold plated connectors and contacts
- Double shielded cable, corrosion resistant tinned copper conductors
- USB 2.0, 480Mbps; 10 year warranty

From the Lines cable connectivity concept developed by Lindy, Anthra Line USB 2.0 Type C to A cables are the professional choice for high performance connections in commercial AV and IT installations.

USB Type C features a reversible connector, so no matter which orientation the cable is inserted, a connection will always be found. This connector allows a fully bi-directional cable with automatic host and device negotiation.

Anthra Line USB 2.0 cables are premium connections that feature double shielded construction with tinned copper conductors for performance and corrosion resistance. High quality gold plated contacts and connectors maintain signal integrity and reliability.

Data transfer speeds up to 480Mbps are supported for the quick and effortless transfer of large data volumes.

Anthra Line USB 2.0 Type C to A cables are available in lengths from 0.5m, 1m, 2m and 3m

Technical details

Connectors

- Connector A: USB 2.0 Type C Male
- Connector B: USB 2.0 Type A Male
- Housing Material: PVC
- Connector Plating: 24K Gold Plated
- Pin Construction: Phosphor Bronze
- Pin Plating: 24K Gold Plated
- Dimensions, USB Type C (approx.) WxDxH: 11.0x25.5x7.3mm [0.43x1.00x0.29in]
- Dimensions, USB Type A (approx.) WxDxH: 15.5x35.1x7.8mm [0.61x1.38x0.31in]

Cable Construction

- Length: 3m [9.84ft]

- Standard: USB 2.0
- Colour: Black
- Type: Round
- Jacket Diameter: 3.5mm (0.14in)
- Jacket Material: PVC
- Conductor Material: Tinned Copper
- Conductor Gauge: 28AWG
- Shielding: Copper Braid 60%

Specifications

- Supported Bandwidth: 480Gbps
- Maximum Resolution: -
- Nominal Attenuation: 0.5-3m: 0.5Mhz – 400Mhz < 5.8db
- Minimum Bend Radius: 35mm (1.38in)
- Operating Temperature: -20°C - 80°C (-4°F - 176°F)
- Storage Temperature: -25°C - 85°C (-13°F - 185°F)

Miscellaneous

- Packaging Type: Polybag
- Warranty (Years): 10
- Certificated: RoHS, REACH, UL

Purchasing Information

- No. 36888
- EAN: 4002888368889

This product is also available in other lengths

- 36885 - 0.5m (1.64ft)
- 36886 - 1m (3.28ft)
- 36887 - 2m (6.56ft)
- 36888 - 3m (9.84ft)