



HDMI to DisplayPort, DVI & VGA Converter

No.: 38182

Connects an HDMI source to a DisplayPort, DVI or VGA monitor

Description

- Converts HDMI signals into DisplayPort, DVI or VGA signals
- Supports Ultra HD resolutions 3840x2160@30Hz for DisplayPort and Full HD 1920x1200@60Hz for DVI/VGA
- Easily connect with a single legacy or modern display at any one time
- Quick and simple plug & play installation
- 2 year warranty

The Lindy HDMI to DisplayPort, DVI and VGA Converter allows users to connect either a DisplayPort, DVI or VGA screen to an HDMI source. Supporting 4K resolutions up to 3840x2160@30Hz on HDMI displays, content can be viewed with superior clarity and stunning accuracy. DVI and VGA monitors are supported with a maximum resolution of 1920x1200@60Hz. The integrated USB cable can be connected to a USB port or USB power supply to power the converter.

With its lightweight, low profile design, this converter easily fits into a notebook bag and simply expands available connectivity options, so users can connect to the most commonly used digital and analogue video equipment, without having to carry multiple adapters - ideal for BYOD applications.

Plug & play, it is quick and easy to use as it can be powered by the included USB cable that connects to either a USB output or a USB power supply.

Technical details

Specifications

- AV Interface: HDMI to DP, DVI & VGA
- Interface Standard: HDMI 1.4, DP 1.2, DVI-D & VGA
- Supported Bandwidth: Max. 3Gbps per lane
- Maximum Input Resolution: 4K@30Hz
- Maximum Output Resolution:
 - DP: 4K@30Hz
 - DVI/VGA: 1920x1200@60Hz
- Chipset: STDP2600, PS8222, AG6200
- HDCP Support: HDCP 1.4
- Supported Audio: 7.1 LPCM digital audio up to 192kHz 24bit
- Separate Audio Ports: -
- Special Features: Optional power via USB

Connectors

- Input: HDMI Type A Male, USB Type A Male (for power)
- Output: DisplayPort Female, DVI-D Female, VGA Female

Physical properties

- Dimensions (approx.) WxDxH:
 - Housing: 86.9x40.02x16.18mm (3.42x1.58x0.64in)
 - HDMI: 45.57x19.86x11.2mm (1.79x0.78x0.44in)
 - USB: 49.55x16.21x7.92mm (1.95x0.64x0.31in)
- Cable Length: 150mm (5.91in)
- Housing Material: ABS
- Jacket Material: ABS
- Jacket Diameter: 5.5mm (0.22in)
- Minimum Bend Radius: 5.5mm (0.22in)
- Net Weight: 0.06kg (0.13lb)
- Operating Temperature: 0°C - 65°C (32°F - 149°F)
- Storage Temperature: -10°C - 125°C (14°F - 257°F)
- Humidity: 20 - 95% RH (non-condensing)
- Colour: Black

Miscellaneous

- Packaging Type: Polybag
- Packaging Dimensions: 160x160x20mm (6.3x6.3x0.79in)
- Gross Weight: 0.07kg (0.15lb)
- Warranty (Years): 2
- Certificated: CE, FCC, RoHS & REACH

Package Contents

- HDMI to DisplayPort, DVI & VGA Converter

Purchasing Information

- No.: 38182
- EAN: 4002888381826