



## 100m Cat.6 HDMI 18G, IR & RS-232 HDBaseT Extender with PoC, Receiver

No.: 38207

Extend 4K signals up to 100m via HDBaseT technology

### Description

- Distributes HDMI resolutions up to 150m over Cat.6 network cable via HDBaseT & Long Reach technology
- Supports HDMI 18G resolutions up to 4K@60Hz 4:4:4, with additional support for HDR
- RS-232, CEC pass-through and bi-directional IR for simple control
- Supports PoC (Power over cable), requiring a power supply connection from only one side of the installation
- 2 year warranty

The Lindy C6 HDBaseT HDMI 18G & IR Extender, Receiver is one part of a high performance solution for extending HDMI signals over long distances via Cat.6 network cable. By combining this receiver unit with a compatible Lindy HDBaseT transmitter, splitter or matrix, this solution ensures reliable transmission up to 150m.

The following distance and resolution combinations are possible when using high quality Cat.6 U/UTP or F/UTP cable:

150m (492.12ft) - 1280x720@60Hz via Long Reach Mode

100m (328.08ft) - 3840x2160@30Hz 4:4:4 8bit

70m (229.66ft) - 3840x2160@60Hz 4:4:4 8bit

Supporting resolutions up to 4K UHD 3840x2160@60Hz, video can be viewed in stunning clarity, while additional support for HDR (High Dynamic Range) allows content to be displayed with enhanced brightness, greater contrasts of blacks and whites and a much wider colour gamut. This provides a reliable solution for creating eye-catching digital signage in retail, immersive displays at events or engaging setups in larger conference rooms or lectures halls. Analogue audio can be easily extracted via 3.5mm port for connecting speakers or amplifiers, to provide dual channel immersive audio to compliment the video content.

PoC (Power over Cable) functionality provides additional flexibility. This allows power to be supplied alongside data through Cat.6 network cable in a point to point connection between the transmitter and receiver, meaning only a single power supply is required at the transmitter unit. Ideal when power outlets are limited at the receiver end of the installation.

Featuring bi-directional IR ports at both sides of the setup, the source equipment can be easily controlled from the display side, and the display can also be controlled from the HDMI source side. Combined with CEC control, which allows commands from one main remote, this extension system allows for complete and simple control for the user. Terminal blocks allows for pass-through of RS-232 commands when integrated into control systems.

HDBaset is a globally recognised standard for high quality distribution of AV content and other technologies, including power and control, over longer distances via low cost Cat.6 or above cable.

HDBaseT™ and the HDBaseT Alliance logo are trademarks of the HDBaseT Alliance.

**Please Note: Due to the methods of compression with this product, it is recommended this item is only used for a point to point connection with 38206.**

## Technical details

### Specifications

- AV Interface: HDMI
- Interface Standard: 2.0
- Supported Bandwidth: 18Gbps
- Maximum Distance:
  - 70m (229.66ft) - 3840x2160@60Hz 4:4:4 8bit
  - 100m (328.08ft) - 3840x2160@30Hz 4:4:4 8bit
  - 150m (492.12ft) - 1280x720@60Hz
- Maximum Resolution: 3840x2160@60Hz 4:4:4 8bit
- HDCP Support: 2.2
- EDID Pass Through: Pass-through
- Supported Audio:
  - HDMI Audio Pass-through
  - 2CH Analogue
- Separate Audio Ports: -
- IR Support: 20KHz - 60KHz
- CEC Support: Pass-through
- Serial Interface: RS-232 (Bi-directional)
- Transmission Protocol: HDBaseT
- Transmission Medium: 1 x Cat.6
- Laser Class (only for Fibre): -
- Wavelength (only for Fibre): -
- Chipset: VS010-A0
- Special Features:
  - 2CH Analogue Audio Extraction
  - PoC (Power over Cat.6)

### Connectors

- Transmitter Input: -
- Transmitter Output: -
- Receiver Input: RJ-45 (Female)
- Receiver Output:
  - HDMI Type A (Female)
  - 3.5mm (Female)
- Bi-directional Ports: RS-232 (Female)
- Power : 5.5/2.1mm

### Physical Properties

- Dimensions (approx.) WxDxH: 140x65x18mm (5.51x2.56x0.71in)
- Housing Material: Metal
- Net Weight: 0.478kg (1.05lb)
- Operating Temperature : 0°C - 40°C (32°F - 104°F)
- Storage Temperature: -20°C - 60°C (-4°F - 140°F)
- Humidity: 20 - 90% RH (non-condensing)
- Power Requirements: 24VDC 1A
- Colour: Black

### Miscellaneous

- Packaging Type: Carton Box
- Packaging Dimensions: 220x115x75mm (8.66x4.53x2.95in)
- Gross Weight: 0.644kg (1.42lb)
- Warranty (Years): 2
- Certificated: CE, FCC, RoHS, REACH & California Proposition 65

### Package Content

- HDBaseT HDMI Extender, Receiver
- IR Emitter Cable, 1.5m
- IR Receiver Cable, 1.5m

- 2 x Mounting Ears
- 3-Pin Terminal Block
- Multi-country Power Supply (UK, EU, US & AUS)
- Lindy Manual

**Purchasing Information**

- No.: 38207
- EAN: 4002888382076

© LINDY 2021