



# 2 Port DisplayPort 1.2, USB 2.0 & Audio Cable KVM Switch

No.: 42344

Switch between 2 DisplayPort equipped PCs from one keyboard, mouse and monitor

## Description

- Control two DisplayPort equipped PCs from a single keyboard, mouse and monitor
- Switch via the unit's push button control, software or keyboard hot keys
- Supports DisplayPort 1.2 signals, up to 4K 60Hz
- · Integrated cables for quick, hassle-free installation
- 2 Year Warranty

The Lindy 2 Port DisplayPort 1.2, USB 2.0 & Audio KVM Switch is a compact solution for providing access and control over two DP equipped PCs from a single keyboard, mouse and monitor. With integrated cables, this switch can be easily connected directly to the system, with no need for purchasing additional cables and saving time on the installation.

Support for resolutions up to 4K Ultra HD 60Hz ensures the optimum image quality, perfect for high graphical content in gaming setups, video editing or dual system control workstations. The audio output port on the main unit also allow users to connect headphones or speaker to add immersive 2CH audio and a microphone, while additional USB peripherals can be integrated with a USB hub.

The KVM switch features multiple switching options including a push button control (with 1.5m cable), hotkey and software switching to provide simple, reliable control for the user, great for both professional and first time users.

Please note: Software control & hotkey switching are not currently compatible with devices supporting macOS 10.15. This is due to an incompatibility between macOS 10.15 and 32-bit software.

# Technical details

#### **Specifications**

- AV Interface: DisplayPort
- Console Interfaces: USB
- Interface Standard: DisplayPort 1.2, USB 2.0
- Maximum Resolution: 4096x2160@60Hz 4:4:4 8bit
- HDCP Support: HDCP 1.4
- Supported Audio: Analogue Stereo
- Separate Audio Ports: 2 x 3.5mm (Female)
- Serial Interface: -
- Console Number: 1
- Max Number PC/Server: 2
- Cascadable: -

- Switching Method: Push Button, Hotkey Switching & Software
- 19" Rack Mountable: -
- Special Features: Supports USB 2.0 Hubs And Device Sharing, Active LED Indicators

#### Connectors

- Console Interfaces: DisplayPort (Female), USB 2.0 Type A (Female), 2 x 3.5mm (Female)
  PC/Server Interfaces: 2 x DisplayPort (Male), USB 2.0 Type A (Male), 2 x 3.5mm (Male) 1.2m Integrated Cables
- Other Interfaces: -
- Power: -

#### **Physical Properties**

- Dimensions (approx.) WxDxH: 97x25x82.18mm (3.82x0.98x3.24in)
- Housing Material: PlasticNet Weight: 0.433kg (0.95lb)
- Operating Temperature: 0°C 40°C (32°F 104°F)
  Storage Temperature: -20°C 60°C (-4°F 140°F)
  Humidity: 0 90% RH (non-condensing)

- Power Requirements: 5V
- Colour: Black

# Miscellaneous

- Packaging Type: Carton BoxPackaging Dimensions: 160x60x250mm (6.3x2.36x9.84in)
- Gross Weight: 0.514kg (1.13lb)
- Warranty (Years): 2
   Certificated: CE, FCC, RoHS, REACH & California Proposition 65

### **Package Contents**

- DisplayPort KVM switch
- Lindy Manual

## **Purchasing Information**

- No.: 42344
- EAN: 4002888423441

© LINDY 2021