



USB 3.1 Type C Hub & Gigabit Ethernet Converter

No.: 43249

3 Port USB Hub & Gigabit Ethernet

Description

- Connects a USB 3.1 Type C computer to a Gigabit Ethernet network
- Provides three USB 3.1 Gen 1 / 3.0 Type A ports
- Supports 10/100/1000BASE-T, full and half duplex mode
- USB 3.1 Gen 1 / 3.0 SuperSpeed data transfer rates up to 5Gbps
- 2 year warranty

The Lindy USB 3.1 Hub & Gigabit Ethernet Converter allows users to conveniently connect a ultrabook, netbook or tablet to a Gigabit Ethernet network via a Type C USB port and also provides three additional USB 3.1 Gen 1 / 3.0 Type A ports.

This converter is ideal for ultrabooks or tablets which do not feature wired network connectivity and may only offer a limited number of USB ports.

With its small size and lightweight design this USB 3.1 Hub & Gigabit Ethernet Converter is easy and convenient to carry, and because it is powered by the USB Bus no power adapter is required. It is backwards compatible with Thunderbolt 3 ports to cover a wide range of devices including MacBooks.

Information about USB 3.0, 3.1 & 3.2

USB 3.0, USB 3.1 and USB 3.2 PCs, cables and devices are all compatible with each other, when using either a USB Type A or USB Type C host interface.

USB 3.0, USB 3.1 Gen 1 and USB 3.2 Gen 1 all support data transfer rates up to 5 Gbps.

USB 3.1 Gen 2 and USB 3.2 Gen 2 both support data transfer rates up to 10 Gbps.

Technical details

Specifications

- Interface: USB to RJ45 & 3x USB Type A
- Interface Standard: USB 3.1 Gen 1 / 3.0, Gigabit LAN
- Supported Bandwidth: 5Gbps, 10/100/1000Mbps
- Chipset: AX88179 (LAN), VL813 (Hub)
- Compatibility: USB Type C equipped computers, Thunderbolt 3 (incl. Apple M1)
- Power Delivery: -
- Special Features: -

Connectors

- Inputs: 1 x USB Type C (Male)
- Outputs: 1 x RJ45 (Female), 3 x USB Type A (Female)
- Power: Bus-powered

Physical Properties

- Dimensions WxDxH: 30x110x20mm (1.18x4.33x0.79in)
- (Fixed) Cable Length: 260mm (10.24in)
- Housing Material: Plastic
- Net Weight: 0.050kg (0.11lb)
- Operating Temperature: 0°C - 50°C (32°F -122°F)
- Storage Temperature: -10°C - 75°C (14°F - 167°F)
- Humidity: 0 - 85% RH (non-condensing)
- Power Requirements: -
- Colour: Black

Miscellaneous

- Packaging Type: Carton Box
- Packaging Dimensions: 135x100x30mm (5.31x3.94x1.18in)
- Gross Weight: 0.1kg (0.22lb)
- Warranty (Years): 2
- Certificated: CE, FCC, RoHS, REACH

Package Contents

- USB 3.1 Hub & Ethernet Converter
- LINDY Manual

Purchasing information

- No.: 43249
- EAN: 4002888432498