



1m Cat.5e U/UTP Network Cable, Grey, 50 pcs

No.: 48406

RJ45, M/M, 100MHz, CCA

Description

- 50x Twisted Pair Patch Cable with RJ45 connectors
- Cat.5e U/UTP, CCA
- Integrated snagless connector for latch protection
- Gold plated pins for better conductivity and elimination of signal loss
- 10 year warranty

Cat.5e U/UTP PVC network cable with support for bandwidth up to 100MHz and features a snagless design with gold plated contacts for ethernet standards up to 1GBase-T.

Cat.5e cable, designed for operating frequencies up to 100MHz. The unshielded version [U/UTP] is designed in its electrophysical parameters [NEXt, FEXt etc.] in such a way that it can be used for Gigabit Ethernet despite the lack of shielding. These cables are manufactured and tested according to the ISO/IEC 11801 specification.

The gold-plated contacts ensure reliable, corrosion-free connections over extensive periods of time. A robust snagless strain relief design prevents damage to the connector latch during installation and removal.

The high frequencies used in network technology cause a high current load in the outer layers of the conductors due to the "skin effect", while the conductor cores are only subjected to very low electrical loads. This allows the use of copper clad aluminium [CCA] conductor material, making this cable more cost-effective than pure copper cables.

Available lengths: 1m, 2m, 3m, 5m.

Technical details

Connectors

- Connector A: RJ45 Male
- Connector B: RJ45 Male
- Housing Material: Polycarbonate
- Connector Plating: -
- Pin Construction: Copper Alloy
- Pin Plating: Gold plated
- Dimensions [approx.] WxDxH: 11.6x22.8x8.3mm [0.46x0.90x0.33in]

Cable Construction

- Length: 1m [3.28ft]
- Colour: Grey
- Type: Cat.5e

- Jacket Diameter: 4.8mm (0.19in)
- Jacket Material: PVC
- Conductor Material: CCA
- Conductor Gauge: 26AWG
- Shielding: -

Specifications

- Supported Bandwidth: 100MHz
- Nominal Attenuation: 24dB/100m @100MHz
- Minimum Band Radius: 57mm (2.24in)
- Operating Temperature: -10°C - 60°C (14°F - 140°F)
- Storage Temperature: -20°C - 75°C (-4°F - 167°F)

Miscellaneous

- Packaging Type: Carton Box
- Warranty (Years): 10
- Certificated: RoHS, REACH, California Proposition 65

Purchasing Information

- No.: 48406
- EAN: 4002888484060

This product is also available in other lengths

- 48406 - 1m (3.28ft)
- 48407 - 2m (6.56ft)
- 48408 - 3m (9.84ft)
- 48409 - 5m (16.44ft)