



DATASHEET

19" Server Cabinets PRO, 800x1000 mm, 1+2-Part Doors



Description

19" server cabinet according to DIN41494

Steel sheet housing with screwed frame, completely pre-assembled, self-ventilated, detachable
Inside front and rear 4 x 19" profiles (2 front, 2 rear-sided), galvanised, step-less depth-adjustable

Contrariwise numbering of rack units at the 19" profiles

Front and rear door with 3-point turning handle (up to 24U 1-point), lockable, incl. profile half-cylinder acc. to
DIN18252 / EN 1303

Profile half-cylinder exchangeable by customer (30/10 mm)

Door stop for front and rear door possible left- or right-sided

Detachable side walls with 2 x latch locking (lock equal to the door lock)

Cabinets stackable side-by-side with and without removal of the side walls, baying set (Art.-No. PRO-ANR0X),
otherwise screwable via screw set M6

Roof and bottom with 4/6 pre-punched openings for cable entry (450 x 90 mm), for 600 mm cabinet width cable
entry only rear

Roof prepared for accommodation of 2-fan or 4-fan units, bottom with pre-punched opening for filter or cable
entry modules

Internal earthing of all cabinet sections

Pre-assembled earthing bar rear-sided in the middle of the cabinet (ports: 20 x M5 + 2 x 8 mm)

Max. load 1000 kg (depths 600 / 800 mm) resp. 1360 kg (depths 1000 / 1200 mm for >24U)

Paint finish RAL9005, jet black

Protection degree IP20

Included accessories: 1 x brush, 1 x set of captive nuts (PU 20 pcs.), earthing bar and earthing cables, 4 x levelling
feet M12, 2 x key

This datasheet was created automatically on 27-04-2020 . Technical changes reserved.



DATASHEET

19" Server Cabinets PRO, 800x1000 mm, 1+2-Part Doors

Delivery in transport packaging on disposable pallet

General data

Type of front door	Steel perforated 1-part
Type of back door	Steel perforated 2-part
Mounting level	Front and rear
Model	With permanent frame
Modular spacing	482,6 mm (19 inch)
Type of profile rail	Crank
Number of doors	2
Type of ventilation	Passive
With roof plate	True
With earthing	True
With front door	True
With backside door	True
With sidewall	True
With socket	False
Material	Steel
Type of surface	With powder coating
Degree of protection (IP)	IP20
Demountable	True

Available variants

Article no.	Title	Number of height units	Width	Depth	Height	Colour	RAL-number
PRO-2780TS.P1P2	19" Server Cabinet PRO 27U, 800x1000 mm, F=1-P R=2-P, RAL9005	27 U	800 mm	1000 mm	1297 mm	Black	9005
PRO-4280TS.P1P2	19" Server Cabinet PRO 42U, 800x1000 mm, F=1-P R=2-P, RAL9005	42 U	800 mm	1000 mm	1963 mm	Black	9005
PRO-4780TS.P1P2	19" Server Cabinet PRO 47U, 800x1000 mm, F=1-P R=2-P, RAL9005	47 U	800 mm	1000 mm	2186 mm	Black	9005

This datasheet was created automatically on 27-04-2020 . Technical changes reserved.

