

Matrox® ConvertIP™ DRS

Dual-channel RJ45 SDI-to-IP transmitter/receiver

Matrox ConvertIP DRS is a compact, standalone ST 2110 and IPMX transmitter/receiver device. Featuring 12G-SDI, genlock, and three RJ45 ports on a single device, ConvertIP DRS is designed for 1G AV workflows and is optimal for an ultra-low latency experience. The device can deliver power over Ethernet through its RJ45 connection, or it can be powered through an optional power supply unit. Both can be used simultaneously to deliver power redundancy.



Technical specifications

Product	
Part Number	CIP-DRS
Form Factor	<ul style="list-style-type: none"> Standalone appliance Rack-mountable: 1U, 1/2 rack (horizontal)
Connectivity	
Video Input	<ul style="list-style-type: none"> Tx mode: 12G SDI Rx Mode: No input
Video Input Resolutions	HD and 4K broadcast resolutions
Video Outputs	<ul style="list-style-type: none"> Tx mode: No output Rx mode: 12G SDI
Video Output Resolutions	HD and 4K broadcast resolutions
Genlock	Bi-Level and Tri-Level input support
VANC ancillary data processing	Yes ¹
Audio Input/Output	<ul style="list-style-type: none"> Up to 16 channels of audio embedded in SDI output signal Unbalanced analog stereo input via 1/8" (3.5mm) jack Line Level
Network Connector	3x RJ45 (LAN 1 for Media and Control with PoE, LAN 2 for Media and Control (redundant), Control LAN for Control data)
RS-232	Yes ²
Control and Management	Web browser-based UI, standalone utility
Performance	
Maximum Video Resolutions	4096 x 2160 60p
Bit Depth and Color Space	<ul style="list-style-type: none"> YCbCr 4:2:0 10-bit³ and 8-bit⁴ YCbCr 4:2:2 10-bit RGB 4:4:4 8-bit SDR/HDR⁵
Video and Audio Processing	
Video Scaling	High Quality multi-tap 10-bit Up/Down Scaler
Video Deinterlacing	Yes
Color Space Conversion	Yes
Encoding formats	
Video ⁶	Default compressed bitrates: 200 Mbps for HD content, 820 Mbps for 4K content <ul style="list-style-type: none"> Colibri codec included. 4:2:2 10-bit YUV and 4:4:4 8-bit RGB, 100 to 2000 Mbps JPEG-XS codec upgrade required.¹⁰ 4:2:2 10-bit YUV and 4:4:4 8-bit RGB, 100 to 2000 Mbps
Audio	Uncompressed PCM (~1 Mbps/ch)
Latency	Less than a 1/4 frame (<4 ms)
Network	
Network Standard	RJ45 providing 1 GbE or 2.5 GbE Base-T Ethernet
IP Addressing	<ul style="list-style-type: none"> IPv4 IPv6⁷ DHCP (default) and static IP
Supported Protocols	<ul style="list-style-type: none"> SMPTE ST 2110 (-10, -20, -21, -22, -30, -31, and -40) SMPTE ST 2059-2 SMPTE ST 2022-7
Redundancy	Yes (ST 2022-7)
Command and Control	HTTPS over TCP
Discovery, Registration and Control	NMOS discovery and control according to standards IS-04 v1.3 and IS-05 v1.1
PoE+	Yes (IEEE 802.3at Type 2)

Physical	
Product Dimensions	7.13 (D) x 7.53 (W) x 1.42 (H) inches 181 (D) x 191 (W) x 36 (H) mm
Unit Weight	1.47lbs / 665g
Cooling	Fanless
Power	<ul style="list-style-type: none"> • Device: Input: 12 volts, max 18 Watts • PoE+ • Optional PSU (sold separately) <ul style="list-style-type: none"> • Line Voltage: 100-240 V a.c., 0.5A • Frequency: 50-60 Hz • Input: IEC320-C14 • Output: DIN4 locking power connector
Hardware and Software	
Hardware Included	ConvertIP DRS appliance
Optional Hardware	ConductIP NMOS-based routing solution (Part #: CDCTIP-MRA)
Accessories (sold separately)	<ul style="list-style-type: none"> • ConvertIP power supply unit (Part #: EPS40WKIT-NA, EPS40WKIT-EU, EPS40WKIT-UK, EPS40WKIT-AU, EPS40W-10PK)⁸ • Rackmount kit⁹ (Part #: RMK-19TR-A) • Angled bracket kit (Part #: RMK-6BRKT-A) • Secure cable solution for HDMI (Part #: SK-SLND-4) • NRG redundant power supply unit (Part #: NRG-5-1DB or NRG-5-2DB)
Software	<ul style="list-style-type: none"> • Matrox ConvertIP Command Center (Web UI) • Matrox ConvertIP Manager (Microsoft® Windows® 10)
Optional software	JPEG-XS codec license
Environmental	
Operating Conditions	Temperature: 0 to 45 degrees Celsius Altitude: 650 hPa (3,580 m) to 1,013 hPa (0 m) Humidity: 20% to 80% non-condensing
Storage Conditions	Temperature: -40 to 70 degrees Celsius Altitude: 192 hPa (12,000 m) to 1,020 hPa (-50 m) Humidity: 5% to 95% non-condensing
General	
EMC/EMI Device Class	Class A
EMC/EMI Compliance	<ul style="list-style-type: none"> • CE (EU) • FCC (USA) • ICES-003 (Canada) • KC (Korea) • RCM (Aus/NZ)
Environmental Compliance	<ul style="list-style-type: none"> • China RoHS • EU RoHS • REACH
Warranty	Three-year limited warranty with free online or telephone support

1. 2. 3. 4. 5. 7. Available in a future software update.

6. Bitrates will vary according to resolution.

8. Part # EPS40W-10PK does not include IEC-C14 power cord. These cables must be sourced locally.

9. Can fit up to two ConvertIP units in a 1RU space.

10. For more information, contact your Matrox Video representative.

Contact Matrox Video

Montreal Headquarters: 1-800-631-4903 (North America), 514-822-6364 (Worldwide) | video@matrox.com

London Office: +44 (1895) 827300

Serving: United Kingdom, Ireland, Benelux, France, Spain, Portugal, Middle East, Africa

Munich Office: +49 89 62170-444

Serving: Germany, Austria, Switzerland, Denmark, Finland, Norway, Sweden, Central and Eastern Europe, the Baltic States, Greece, Turkey, Italy

© 2022 Matrox Graphics, Inc. All rights reserved. Matrox reserves the right to change specifications without notice. Contact Matrox for more details on specific requirements. Matrox and Matrox product names are registered trademarks in Canada or other countries and/or trademarks of Matrox Electronic Systems, Ltd and/or Matrox Graphics Inc. All other company and product names are registered trademarks and/or trademarks of their respective owners. 12/2022

