

DATASHEET

Splicebox sliding unit, with E2000® plastic adapter slanted outlet and stripped pigtails, OS2



Description

completely assembled splice box with adapters and coloured pigtails
 metal housing depth adjustable
 cable entries at the rear, incl. 1 x PG16
 6 x self adhesive fiber tray

Special assembly possible at short notice!

General data

Mounting method	482.6 mm (19 inch)-installation
With housing	True
With front plate	True
With pigtails	True
Number of height units	1
Type of connector external	E2000®
Type of connector interior	E2000®
Pigtails prepared	stripped
Sliding	sliding version
Note	Diagonal outlet
Fibre type	Singlemode
Fibre class	OS2
Adapter material	Plastic adapter

This datasheet was created automatically on 18-11-2020 . Technical changes reserved.



DATASHEET

Splicebox sliding unit, with E2000® plastic adapter slanted outled and stripped pigtails, OS2

Dimensions

Height	44.5 mm
Width	483.0 mm
Depth	244.0 mm

Available variants

Article no.	Title	Pigtail	With number of couplings/adapters	Adapter colour	Suitable for number of couplings/adapters	Colour	RAL-number
BA71533SA.12	Splicebox E2000®/APC 9/125µ a., 12 Pigtails /12 Adapter	12 x E2000®/APC	12	green	12	grey	7035

accessory

53012.1	Cable Glands, Standard
80362.2-10	FO Marking Strips "Warnung vor Laserstrahlung"
53010.5	Cable gland PG-16
39926.1	Miller® Fiber Cleaning Tapes

This datasheet was created automatically on 18-11-2020 . Technical changes reserved.

