

DATASHEET

RJ45 Hirose Connector Set STP, TM11 Cat.5e beige



HRS HIROSE
ELECTRIC
GMBH

Cat.5E

Description

Up to 100 MHz (Cat.5e)
For stranded wires (AWG 24/7, AWG 26/7, AWG 27/7)
Shielded version
Core insulation about 0.9 - 1.0 mm
Cable diameter max. 5.8 mm
The set consists of RJ plug, anti-kink sleeve and guide plate
Suitable crimping tool DCW1002 + DCW1002.1 or 39934.2

General data

Category	5E
Model	jack (jack)
Connection type	crimp
Type of connector	RJ45 8(8)
Screened	True
AWG-range for litz wire conductor	24 - 27
Special tool necessary	True
Suitable for round cable	True
Suitable for flat cable	False
Suitable for litz wire conductor	True
Suitable for solid core	False

Available variants

Article no.	Title	Colour
H7540.1-1	RJ45-Hirose TM11 beige 1 pcs.	beige
H7540.1-50	RJ45-Hirose TM11 beige 50 pcs.	beige
H7540.1-100	RJ45-Hirose TM11 beige 100 pcs.	beige

This datasheet was created automatically on 18-11-2020 . Technical changes reserved.



DATASHEET

RJ45 Hirose Connector Set STP, TM11 Cat.5e beige

accessory

DCW1002.1	Die inserts for DCW1002 Crimping Tool
DCW1002	Crimping tool for exchangeable die inserts (DCW1002.x)
39934.1	Crimping Tool for RJ45 Hirose TM11/21/31 Plug

This datasheet was created automatically on 18-11-2020 . Technical changes reserved.



EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

