

DATASHEET

RJ45 Stewart Connector STP, SS39200-012 Cat.6

Cat.6



Description

Up to 250 MHz (Cat.6)
 For stranded wires (AWG 24/7, AWG 26/7,
 AWG 27/7)
 Shielded version
 Core insulation about 0.9 - 1.0 mm
 Cable diameter max. 6.3 mm
 The set consists of RJ plug, and guide plate
 Suitable crimping tool DCW1002 + DCW1002.2

Anti-kink sleeve not included

General data

Category	6
Model	jack (jack)
Connection type	crimp
Type of connector	RJ45 8(8)
Screened	True
AWG-range for litz wire conductor	24 - 27
AWG-range for solid core	24 - 27
Special tool necessary	True
Suitable for round cable	True
Suitable for flat cable	False
Suitable for litz wire conductor	True
Suitable for solid core	False

Available variants

Article no. Title

Colour

This datasheet was created automatically on 24-11-2020 . Technical changes reserved.



DATASHEET

RJ45 Stewart Connector STP, SS39200-012 Cat.6

37563.T	RJ45 Stewart Connector STP, SS39200-012 Cat.6, without anti-kink sleeve	transparent
---------	---	-------------

accessory

37515.27-100	SS39 STP Anti-kink sleeve
DCW1002.2	Die inserts for DCW1002 Crimping Tool
DCW1002	Crimping tool for exchangeable die inserts (DCW1002.x)

This datasheet was created automatically on 24-11-2020 . Technical changes reserved.

