

S-4601

Portable HDMI to SDI converter



■ Introduction:

The S-4601 is a portable HDMI to 3G/HD/SD-SDI converter. It supports HDMI audio embedded into SDI output, and analog audio (3.5mm socket) input, embedded into SDI output.

The S-4601 is heavy duty housing design, protecting the BNC connectors well, and supplied various screw threads in the bottom, for convenient installing, and future accessories (battery mount, etc)



■ Specifications:

Input/Output		
Input	HDMI × 1	HDMI input
	3.5mm × 1	Analog audio input
Output	BNC × 2	Converted 3G/HD/SD-SDI output

Video Format		
SDI	SMPTE-425M	1080p (60 / 59.94 / 50)
	SMPTE-274M	1080p (30 / 29.97 / 25 / 24 / 23.98)
		1080i (60 / 59.94 / 50)
	SMPTE-RP211	1080psf (30 / 29.97 / 25 / 24 / 23.98)
	SMPTE-296M	720p (60 / 59.94 / 50)
	ITU-R BT.656	576i (50)
HDMI	SMPTE-125M	480i (59.94)
		480i / 576i
		1080i (60 / 59.94 / 50)
		720p (60 / 59.94 / 50)
		1080p (60 / 59.94 / 50 / 30 / 29.97 / 25 / 24 / 23.98)
Audio		48KHz Sync

General	
Power	≤ 3W
Working Voltage	DC 6-18V
Working Environment	Temperature: 0°C-+70°C, Humidity:10%-90%
Dimensions	98 × 84 × 29 mm
Net weight	210g

■ Features:

- ◆ Portable HDMI to 3G/HD/SD-SDI Converter
- ◆ 1 HDMI input, 2 SDI output, 1 analog audio input
- ◆ Embed HDMI audio into SDI output
- ◆ Embed Analog audio into SDI output
- ◆ Power/input/output status indicator
- ◆ Pole-tap 6-18V DC power input
- ◆ Heavy duty aluminium housing
- ◆ Bottom screw threads for installing

SWIT Electronics Co., Ltd.

Website:www.swit.cc
Email:contact@swit.cc
Tel:+86 2585805753
Fax:+86 2585805296

Distributed by: