

USB C Multiport Video Adapter with HDMI, VGA, Mini DisplayPort or DVI - USB Type C Monitor Adapter to HDMI 1.4 or mDP 1.2 (4K) - VGA or DVI (1080p) - Rose Gold Aluminum

Product ID: CDPVDHMDPRG



This rose gold USB-C™ multiport video adapter offers a portable solution for connecting your USB Type-C laptop to a VGA, DVI, HDMI® or Mini DisplayPort display. The adapter is also available in [silver \(CDPVGDVHMDMP\)](#) and [space gray \(CDPVDHMDPSG\)](#).



All-in-One Video Connectivity with Travel in Mind

Avoid the hassle of carrying different adapters for different displays with this 4-in-1 USB-C adapter. With VGA, DVI, HDMI and mDP output, you can connect your laptop to virtually any display, a convenient plug-and-play solution for travel or Bring Your Own Device (BYOD) applications.



Astonishing Picture Quality

The HDMI and mDP outputs on this USB-C video adapter support UHD 4K resolutions, providing four times the picture quality of high-definition 1080p. All of the outputs (HDMI, mDP, VGA, DVI) can support high-definition resolutions of up to 1920 x 1200.

Stylish Connectivity

The USB Type-C adapter has an aluminum housing designed to match your rose gold MacBook and is compatible with any device that supports USB-C DP Alt Mode. Featuring a built-in USB-C cable with magnetic cable manager, the USB-C video adapter conveniently stores away for easy travel.

The CDPVDHMDPRG is backed by a StarTech.com 3-year warranty and free lifetime technical support.



Certifications, Reports and Compatibility



Applications

- Connect to virtually any display while traveling
- Connect your BYOD MacBook to a VGA, DVI, HDMI or mDP display at work or school
- Connect a secondary VGA, DVI, HDMI or mDP monitor to your MacBook

Features

- 4-IN-1 MULTIPORT USB-C VIDEO ADAPTER: USB-C DP Alt Mode to any one of HDMI 1.4 (4K 30Hz & 7.1ch audio), mDP 1.2 (4K 60Hz & 2ch audio), VGA or DVI (1080p), HDCP 2.2/1.4, Thunderbolt 3 compatible
- TOUGH & PORTABLE: Durable aluminum Rose Gold enclosure with a magnetically-secured hideaway cable wrap for on-the-go users in the office, at home, boardrooms, and classrooms
- COMPATIBILITY: USB-C display adapter for Dell XPS/Precision/Latitude, Lenovo ThinkPad X1 Carbon/Extreme, Surface Laptop 3/Surface Book 3, TB3 MacBook Pro/Air, HP EliteBook/Spectre/ZBook, Chromebooks
- TESTED & VERIFIED: USB Type-C adapter tested @ 4K mini DisplayPort (60Hz)/HDMI (30Hz) or 1080p VGA/DVI with TV, monitor & projector brands like Dell, Asus, Acer, LG, Samsung, Sharp, Sony, Epson
- EASY TO USE: Supporting a driverless plug-and-play setup, this adapter is fully compatible with multiple OS platforms: Windows / macOS / Linux / Chrome OS

| | | |
|--------------------|-----------------------------------|--|
| Hardware | Warranty | 3 Years |
| | Active or Passive Adapter | Active |
| | Adapter Style | Adapters |
| | AV Input | USB-C |
| | AV Output | DVI-I (Digital Only) - Single-Link HDMI - 1.4 VGA Mini DisplayPort - 1.2 |
| | Chipset ID | Cypress - CYPD1120 Cypress - CY7C65210 Parade - PS8348B Parade - PS171 |
| Performance | Audio Specifications | HDMI - 7.1 Channel Audio DVI - No Audio Support VGA - No Audio Support Mini DisplayPort - 5.1 Channel Audio |
| | Maximum Analog Resolutions | 1920 x 1200 @ 60Hz |
| | Maximum Cable Distance To Display | 49.9 ft [15.2 m] |
| | Maximum Digital Resolutions | 3840 x 2160 @ 30Hz |
| | MTBF | 654,111 hours |
| | Supported Resolutions | Max HDMI output: 3840 x 2160 @ 30Hz Max mDP output: 3840 x 2160 @ 60Hz HDMI and mDP output: 3840 x 2160, 2560 x 1600, 1920 x 1200, 1920 x 1080, 1280 x 720 DVI and VGA output: 1920 x 1200, 1920 x 1080, 1280 x 720 |
| | Wide Screen Supported | Yes |
| | Connector(s) | Connector A |
| Connector B | | 1 - Mini-DisplayPort (20 pin) Female Output 1 - VGA (15 pin, High Density D-Sub) Female Output 1 - DVI-D (25 pin) Female Output 1 - HDMI (19 pin) Female Output |

| | | |
|-------------------------------------|---------------------------|--|
| Special Notes / Requirements | Note | <p>Only one video output is supported on the video adapter at a time, if multiple connections are made, only one of the outputs will function</p> <p>Maximum Cable Distance to Display refers to digital video. VGA distance capabilities are dependent upon the quality of your cabling</p> |
| Environmental | Humidity | <p>Storage: 5% ~ 90 % RH (no condensation) Operating: 10% ~ 85 % RH (no condensation)</p> |
| | Operating Temperature | 0°C to 45°C (32°F to 113°F) |
| | Storage Temperature | -10°C to 70°C (14°F to 158°F) |
| Physical Characteristics | Cable Length | 4.5 in [115 mm] |
| | Color | Rose Gold |
| | Material | Aluminum |
| | Product Height | 0.6 in [1.5 cm] |
| | Product Length | 6.7 in [16.9 cm] |
| | Product Width | 5.6 in [14.2 cm] |
| | Weight of Product | 6.4 oz [180 g] |
| Packaging Information | Package Height | 0.6 in [16 mm] |
| | Package Length | 2.2 in [55 mm] |
| | Package Width | 4.1 in [10.5 cm] |
| | Shipping (Package) Weight | 0.2 lb [0.1 kg] |
| What's in the Box | Included in Package | 1 - travel A/V adapter |

Product appearance and specifications are subject to change without notice.