



## 2 Port DisplayPort 1.2, USB 2.0 & Audio KVM Switch

No.: 39304

Switch between 2 DP equipped PCs from one keyboard, mouse and monitor

### Description

- Controls two DisplayPort equipped PCs from a single keyboard, mouse and monitor
- Switch via the unit's push buttons or keyboard hot keys
- Supports DisplayPort 1.2 signals, up to 4K 60Hz
- Independent audio switching and 2 ports USB 2.0 Hub for sharing additional USB peripherals
- 2 year warranty

A KVM switch allows an operator to conveniently control and manage multiple devices, such as PCs and servers, from a single keyboard, mouse and display console.

The Lindy 2 Port DisplayPort 1.2, USB 2.0 & Audio KVM Switch is a compact solution for providing access and control over two DP equipped PCs from a single keyboard, mouse and monitor.

Support for resolutions up to 4K Ultra HD 60Hz ensures the highest image quality, perfect for demanding graphical content in gaming setups, video editing or quad system control workstations. The audio output ports on the main unit also allow users to connect headphones or speakers to add immersive 2CH audio and a microphone, while additional USB peripherals can be integrated with the 2 ports USB 2.0 hub. Both audio and USB hubs can be switched independently of the computers allowing users to print from one PC whilst working on another for example.

It supports True Transparent USB switching, an advanced USB emulation technology that allows the KVM to recognise specific keyboard & mouse models and emulate any of their associated special key and function information. This also provides enhanced support for combined use with KVM extenders.

The KVM switch features multiple switching options including push buttons on the unit and configurable hotkeys that provide simple, reliable control for the user, great for both professional and first time users.

Please Note: connection cables are not included, we suggest to use DP cables up to 1m and USB 2.0 Type A/B cables up to 5m to reach the highest resolutions and best performances. Active converters and MST hubs are not supported.

### Technical details

#### Specifications

- AV Interface: DisplayPort
- Console Interfaces: USB
- Interface Standard: DisplayPort 1.2, USB 2.0
- Maximum Resolution: 3840x2160@60Hz

- HDCP Support: -
- Supported Audio: Analogue Stereo
- Separate Audio Ports: 2 x 3.5mm [Female]
- Serial Interface: -
- Console Number: 1
- Max Number PC/Server: 2
- Cascadable: Yes
- Switching Method: Port Buttons & Hotkey Switching
- 19" Rack Mountable: -
- Special Features: USB 2.0 Hub, Independent audio and Hub switching, Active LED Indicators

#### Connectors

- Console Interfaces: DisplayPort [Female], USB Type A HID [Female], 2 x 3.5mm [Female]
- PC/Server Interfaces: 2 x DisplayPort [Female], USB 2.0 Type B [Female], 2 x 3.5mm [Female]
- Other Interfaces: 2 x USB 2.0 Type A [Female] Shared Ports
- Power: 5.5/2.1mm DC socket

#### Physical Properties

- Dimensions WxDxH: 165x45x105mm [6.5x1.77x4.13in]
- Housing Material: Metal
- Net Weight: 0.6kg [1.32lb]
- Operating Temperature: 0°C - 50°C [32°F - 122°F]
- Storage Temperature: -20°C - 60°C [-4°F - 140°F]
- Humidity: 0-90% RH [non-condensing]
- Power Requirements: 9VDC 1.1A
- Colour: Silver

#### Miscellaneous

- Packaging Type: Carton box
- Packaging Dimensions: 250x170x70mm [9.84x6.69x2.76in]
- Gross Weight: 1kg [2.2lb]
- Warranty [Years]: 2
- Certificated: CE, FCC, RoHS & REACH

#### Package Contents

- KVM Switch
- Multi-Country PSU [UK, Euro, US, AUS]
- Lindy Manual

#### Purchasing Information

- No.: 39304
- EAN: 4002888393041