



SNE SERIES RACK, SNE30D-4542-P2

SNE30D-4542-P2 |

FEATURES & BENEFITS

The SNE Series Digital is configured for digital (IP based) security systems consisting of high-density cabling, network equipment, and servers. Optional Tool-Free Lever Lock™ system accommodates small devices including encoders, power supplies, and Access Control Systems. • Fully configured Security Network Enclosure with passive ventilation for data centers o 70% open area vented front door o Pair of split flush mount locking side panels o 2 pair of adjustable cage-nut rackrail (including 6mm hardware) o Lever Lock™ compatible (accepts all Lever Lock™ vertical 21" accessories) o 30" width o 42" overall depth o 45 rackspace o 100 6mm cage-nuts/rack screws included SNE Series Digital with passive chimney cooling • Solid split rear door • Chimney top • Front air-dam • Solid bottom with air-diverter



- Lever Lock™ compatible (accepts all 21" vertical accessories)
- UTL/ETL listed and seismic certified
- Configured for passive chimney cooling
- Includes 70% open front door and solid split rear door
- Includes chimney top, solid bottom, and front air dams
- Includes pair of split flush mount locking side panels
- Includes 2 pair of adjustable cage-nut rackrail
- Includes 100 6mm cage nuts and rack screws
- Includes 4 leveling feet
- Includes 4 casters

SPECIFICATIONS

GENERAL INFO

Gangable: Yes
Finish: Black Powder Coat
UL Standards Tested: UL2416

Component Type: Passive

LISTING AGENCIES/THIRD PARTY CERTIFICATIONS

Greenguard: Yes

ETL Listed: Yes

UL Listing No: E313734

UL Standard: Yes

DIMENSIONS

Usable Depth: 38.48

Usable Height: 78.75

Panel Width: 19

Depth (US): 43.15

Height (US): 117.77

Width (US): 30

Rack Units: 45

TECHNICAL INFORMATION

Rackrail Type: Cage Nut

Static Load Capacity: 12000

UL Load Capacity: 3000

Material: Steel

Mounting: Horizontal

Seismic Rating: Yes