



4 Port HDMI 4K Quad View KVM Switch Pro

No.: 32329

Full Control of 4 HDMI & USB sources from a 4K console

Description

- Allows you to connect up to 4 Full HD & USB HID source devices and be displayed and controlled at the same time from a 4K console
- Supports HDMI 2.0 4K@60Hz 4:4:4 8bit video resolutions & HDCP 1.4 on the output port
- Supports full screen mode with realtime 4K upscaling and seamless switching between the sources
- 2 Year Warranty

This 4K HDMI KVM switch with Quad View feature is able to display 4 FullHD sources like PC, servers or PVR systems at the same time on a 4K display or projector and switch to a full screen mode with source video signal upscaling in realtime. The user is able to interact with each attached device by simply moving the mouse pointer from one quadrant to another and switch to a full screen view as needed by double clicking the mouse's scroll wheel.

It's also possible to increase the number of the controlled sourced installing more switches in a cascade configuration. Thanks to seamless switching capabilities switching from one source to another is completed instantly without any black screen or screen freezing, making it perfect for mission critical applications such as a control room installation.

Technical details

Specifications

- AV Interface: HDMI
- Console Interfaces: USB
- Interface Standard: HDMI 2.0, USB 1.1
- Maximum Resolution:
 - Input: 1920x1080@60Hz
 - Output: 4K60Hz
- HDCP Support: HDCP 1.4
- Supported Audio: Stereo LPCM and Multichannel Dolby Digital, DTS, Dolby TrueHD, DTS-HD (HDMI Embedded)
- Separate Audio Ports: -
- Serial Interface: Yes
- Console Number: 1
- Max Number PC/Server: 4
- Cascadable: Yes
- Switching Method: Port Buttons, Hotkey Switching (Hotkey Configurable), Serial Interface
- 19" Rack Mountable: Yes (1U - Rack Mount Brackets Included)
- Special Features: -

Connectors

- Console Interfaces: 1 x HDMI (Female), 2 x USB Type A HID (Female)

- PC/Server Interfaces: 4 x HDMI (Female), 4 x USB 1.1 Type B (Female)
- Other Interfaces: -
- Power: 5.5/2.1mm DC socket

Physical Properties

- Dimensions (approx.) WxDxH: 438x200x44mm [17.32x7.87x1.77in]
- Housing Material: Metal
- Net Weight: 2.7kg [5.95lb]
- Operating Temperature: 0°C - 40°C [32°F - 104°F]
- Storage Temperature: -20°C - 60°C [-4°F - 140°F]
- Humidity: 0% - 90% RH [non-condensing]
- Power Requirements: 12VDC 5A
- Colour: Black

Miscellaneous

- Packaging Type: Carton box
- Packaging Dimensions: 570x245x105mm [22.44x9.65x4.13in]
- Gross Weight: 3.64kg [8.02lb]
- Warranty (Years): 2
- Certificated: CE, FCC, RoHS & REACH

Package Contents

- KVM Switch
- 2 x 19" Rack Mount Bracket With Screws
- IEC Power Adapter Including IEC Mains Cable
- LINDY Manual

Purchasing Information

- No.: 32329
- EAN: 4002888323291