DATASHEET

DVI 24+1 Dual Link Industrial Connection Cable

Description

Shielding: foil + braiding
Conductor: bare copper, Jacket: PVC
Tinned plugs and gold plated contacts, **housing with full-metal shielding and moulded, for ideal shielding characteristics in rough industrial environment.**
Both sides assembled with ferrite core to dejam signals in the cable (for better EMC characteristics)
Dual link cable
Support for resolution up to 2560 x 1600

General data

Type of connector connection 1	DVI
Number of poles connection 1	25
Connection type connection 1	Plug
Type of connector connection 2	DVI
Number of poles connection 2	25
Connection type connection 2	Plug

Available variants

Article no.	Title	Colour	Length
K5434IND.2	DVI Monitor cable Dual Link, DVI-Digital 24+1, AWG28, 2m	black	2.0 m
K5434IND.3	DVI Monitor cable Dual Link, DVI-Digital 24+1, AWG28, 3m	black	3.0 m

This datasheet was created automatically on 18-11-2020 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

DVI 24+1 Dual Link Industrial Connection Cable

K5434IND.5	DVI Monitor cable Dual Link, DVI-Digital 24+1, AWG28, 5m	black	5.0 m

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION